

FEATURES PXO (Quarzoszillatoren)

- HIGH RELIABILITY FOR LOW COST
- FREQUENCY STABILITY TO ± 25 PPM
- AVAILABLE IN 5.0 AND 3.3 VOLT
- STANDARD DIP 14 AND DIP 8 PACKAGE
- EXCELLENT CLOCK SIGNAL GENERATOR FOR DSP'S AND CPU'S
- EXTENDED TEMPERATURE RANGE TO $-40/+85^{\circ}\text{C}$



PETERMANN

TECHNIK

Time & Frequency Components


SERIES			CXOF	CXOH
PACKAGE			14 PIN DIP	8 PIN DIP
FREQUENCY RANGE			1.0 ~ 80.0 MHz	
FREQUENCY STABILITY			+25 ~ +-100 ppm	
OPERATING TEMPERATURE RANGE			0/+70°C ~ -40/+85°C	
INPUT		VOLTAGE	+5.0 VDC +-10%	
			+3.3 VDC +-10%	
		CURRENT	1 ~ 4.0 MHz = 10 mA max.	
			4.0 ~ 32.0 MHz = 30 mA max.	
32.0 ~ 80.0 MHz = 45 mA max.				
OUTPUT	SYMMETRY	STANDARD	40/60%	
		OPTION	45/55%	
	RISE AND FALL TIME		5 ns typical / 10 ns max.	
	"0" LEVEL	TTL 5 VOLT	0.4 V max.	
	"1" LEVEL		+2.4 V min.	
	"0" LEVEL	CMOS 5 VOLT	0.4 V (10% VDD)	
	"1" LEVEL		+4.5 V (90%VDD)	
	"0" LEVEL	TTL 3.3 VOLT	0.4 V max.	
	"1" LEVEL		+1.4 V min.	
	"0" LEVEL	CMOS 3.3 VOLT	0.1 V (10% VDD)	
	"1" LEVEL		+2.97 V (90%VDD)	
	LOAD	TTL	1 ~ 10 TTL	
		CMOS	15 ~ 50 pF	
PIN 1		STANDARD	WITHOUT ENABLE/DISABLE FUNCTION	
		OPTION	WITH ENABLE/DISABLE FUNCTION	
OTHER PARAMETERS ARE AVAILABLE ON REQUEST / CREATE HERE YOUR SPECIFICATION				

PART NUMBERING SYSTEM


EXAMPLE	CXOH-3-S-E-50-W-27.000MHz
---------	---------------------------

SERIES	CXOF OR CXOH
INPUT VOLTAGE	BLANK FOR 5 VOLT
	3 FOR 3.3 VOLT
SYMMETRY	BLANK FOR 40/60%
	S FOR 45/55%
PIN 1 ENABLE/DISABLE	BLANK FOR NO E/D
	E FOR E/D
FREQUENCY STABILITY	BLANK FOR 100 PPM
	ANY 50 ~ 15 PPM
TEMPERATURE RANGE	BLANK FOR $0/+70^{\circ}\text{C}$
	N = $-10/+60^{\circ}\text{C}$
	M = $-20/+70^{\circ}\text{C}$
	W = $-40/+85^{\circ}\text{C}$


OUTLINE DRAWING OF DIP 14 PACKAGE




OUTLINE DRAWING OF DIP 8 PACKAGE




TEST CIRCUIT FOR CMOS



TEST CIRCUIT FOR TTL



CMOS OUTPUT WAVE FORM



TTL OUTPUT WAVE FORM

