

CM-series

4614 800

Product description

Robust, universal circular connector for control lead connections in hydraulic- and pneumatic systems and in special machinery engineering.

- Compatible with connectors according to MIL-C 5015 resp. VG 95 342









- Housing made of impact-resistant plastic, glass-fibre-reinforced, with screw locking systems for trouble-free, permanent connections

- Easy handling for a quick assembly with integrated strain relief











Basic data

Operating voltage: 50 V AC / DC
Operating current: max. 16 A
Protection class: IP 67
Pollution severity class: 3
Outer cable diameter: 8mm - 14mm
Contact surface: Cu Zn/Ag
Type of connection: solder

1007 84V 03 APR 2001
FAXED

Type		Number of poles	Description	Order no.
 CM 06 EA 14S-7 S		3	Cable socket, straight design, strain relief by means of a clamp Operating current: 10 A	933 049-100
 CM 06 EA 14S-2 S		4	Cable socket, straight design, strain relief by means of a clamp Operating current: 10 A	932 457-100
 CM 06 EA 14S-5 S		5	Cable socket, straight design, strain relief by means of a clamp Operating current: 10 A	932 841-100
 CM 06 EA 14S-6 S		6	Cable socket, straight design, strain relief by means of a clamp Operating current: 10 A	932 458-100



Type		Number of poles	Description	Order no.
 CM 06 EA 14S-61 S		6 + PE	Cable socket, straight design, strain relief by means of a clamp Operating voltage: 10 A	932 460-100
 CM 06 EA 20-15 S		7	Cable socket, straight design, strain relief by means of a clamping cage Operating current: 16 A	933 052-100
 CM 06 EA 20-7 S		8	Cable socket, straight design, strain relief by means of a clamping cage Operating current: 10 A	932 842-100
 CM 06 EA 20-27 S		14	Cable socket, straight design, strain relief by means of a clamping cage Operating current: 5 A	933 067-100
 CM 06 EA 20-29 S		17	Cable socket, straight design, strain relief by means of a clamping cage Operating current: 4 A	933 068-100