


PNP SILICON TRANSISTOR

CSA 643



**TO-92
Plastic Package**

Audio Frequency General Purpose Power Amplifier Application

Complementary CSD 261

ABSOLUTE MAXIMUM RATINGS (Ta=25°C unless specified otherwise)

DESCRIPTION	SYMBOL	VALUE	UNIT
Collector Emitter Voltage	V_{CEO}	20	V
Collector Base Voltage	BV_{CBO}	40	V
Emitter Base Voltage	V_{EBO}	5	V
Collector Current Continuous	I_C	500	mA
Peak	I_{CM}	700	mA
Collector Power Dissipation	P_C	500	mW
Derate Above 25°C		4.0	mW/°C
Operating and Storage Junction Temperature Range	T_j, T_{stg}	-55 to +150	°C

ELECTRICAL CHARACTERISTICS (Ta=25°C unless specified otherwise)



DESCRIPTION	SYMBOL	TEST CONDITION	MIN	MAX	UNIT
Collector Emitter Breakdown Voltage	BV_{CEO}	$I_C=10mA, I_B=0$	20		V
Collector Base Breakdown Voltage	BV_{CBO}	$I_C=100\mu A, I_B=0$	40		V
Emitter Base Breakdown Voltage	BV_{EBO}	$I_E=100\mu A, I_C=0$	>5		V
Collector Cut off Current	I_{CBO}	$V_{CB}=25V, I_E = 0$		0.1	μA
Emitter Cut off Current	I_{EBO}	$V_{EB}=3V, I_C = 0$		0.1	μA
DC Current Gain	h_{FE}	$V_{CE}=1V, I_C=100mA^*$	40	400	
Base Emitter Saturation Voltage	$V_{BE(sat)}^*$	$I_C=500mA, I_B= 50mA^*$		1.3	V
Collector Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=500mA, I_B=50mA^*$		0.4	V

*Pulse Condition: = Width \leq 300us, Duty Cycle \leq 2%.

h_{FE} CLASSIFICATION	R	O	Y	G
	40-80	70-140	20-240	200-400

TO-92 Plastic Package


TO-92 Transistors on Tape and Ammo Pack



- PIN CONFIGURATION**
1. COLLECTOR
 2. BASE
 3. EMITTER

DIM	MIN.	MAX.
A	4.32	5.33
B	4.45	5.20
C	3.18	4.19
D	0.41	0.55
E	0.35	0.50
F	5 DEG	
G	1.14	1.40
H	1.14	1.53
K	12.70	—
L	1.982	2.082

All diminsions in mm.



All dimensions in mm

ITEM	SYMBOL	SPECIFICATION				REMARKS
		MIN.	NOM.	MAX.	TOL.	
BODY WIDTH	A1	4.0	4.8			
BODY HEIGHT	A	4.8	5.2			
BODY THICKNESS	T	3.9	4.2			
PITCH OF COMPONENT	P	12.7			± 1.0	CUMULATIVE PITCH ERROR 1.0 mm/20 PITCH
FEED HOLE PITCH	Po	12.7			± 0.3	
FEED HOLE CENTRE TO COMPONENT CENTRE	P2	6.35			± 0.4	TO BE MEASURED AT BOTTOM OF CLINCH
DISTANCE BETWEEN OUTER LEADS	F	5.08			+ 0.6 - 0.2	
COMPONENT ALIGNMENT SIDE VIEW	Δh	0	1.0			AT TOP OF BODY
COMPONENT ALIGNMENT FRONT VIEW	Δh1	0	1.3			AT TOP OF BODY
TAPE WIDTH	W	18			± 0.5	
HOLD-DOWN TAPE WIDTH	Wo	6			± 0.2	
HOLE POSITION	W1	9			+ 0.7 - 0.5	
HOLD-DOWN TAPE POSITION	W2	0.5			± 0.2	
LEAD WIRE CLINCH HEIGHT	Ho	16			± 0.5	
COMPONENT HEIGHT	H1		23.25			
LENGTH OF SNIPPED LEADS	L		11.0			
FEED HOLE DIAMETER	Do		4		± 0.2	
TOTAL TAPE THICKNESS	t		1.2			t1 0.3-0.6
LEAD - TO - LEAD DISTANCE	F1, F2	2.54			+ 0.4 - 0.1	
STAND OFF	H2	0.45	1.45			
CLINCH HEIGHT	H3		3.0			
LEAD PARALLELISM	C1 - C2		0.22			
PULL - OUT FORCE	(P)		6N			

NOTES

1. Maximum alignment deviation between leads will not to be greater than 0.2mm.
2. Maximum non-cumulative variation between tape feed holes shall not exceed 1 mm in 20 pitches.
3. Holddown tape will not exceed beyond the edge(s) of carrier tape and there shall be no exposure of adhesive.
4. There will be no more than three (3) consecutive missing components in a tape.
5. A tape trailer, having at least three feed holes are provided after the last component in a tape.
6. Splices should not interfere with the sprocket feed holes.

Packing Detail

PACKAGE	STANDARD PACK		INNER CARTON BOX		OUTER CARTON BOX		
	Details	Net Weight/Qty	Size	Qty	Size	Qty	Gr Wt
TO-92 Bulk	1K/polybag	200 gm/1K pcs	3" x 7.5" x 7.5"	5K	17" x 15" x 13.5"	80K	23 kgs
TO-92 T&A	2K/ammo box	645 gm/2K pcs	12.5" x 8" x 1.8"	2K	17" x 15" x 13.5"	32K	12.5 kgs

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Discrete Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD is believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Discrete Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of
Continental Device India Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.
Telephone + 91-11-579 6150 Fax + 91-11-579 9569, 579 5290
e-mail sales@cdil.com www.cdil.com