

This Dicon Linkable Photoelectric Smoke and Fire Alarm is a 9 volt battery powered device utilising a sensing technology that "sees" smoke. This makes the unit ideal for detecting slow smouldering fires. The alarm can be linked to as many as 11 other alarms. This extends security economically over a large area. Pressing and holding the test button confirms the link is operating.

678004

## **FEATURES**

- 9 volt BATTERY POWERED
- Can be linked to as many as 11 other alarms
- Photoelectric sensing technology most sensitive to smouldering fires
- Battery included
- Low battery warning
- Sensitivity Test Button
- LED Operating Indicator
- Loud Piezo Electric alarm





## TECHNICAL SPECIFICATIONS

Sensitivity:

BS5446 Part 1:1990

Sensor:

Photoelectric

Battery Life:

One year

under normal conditions

Low Battery Signal:

Up to 30 days

Alarm Sound Level:

85dB at 3 m

Indicator Light:

Solid-state LED flashes once

every 45 seconds

Interlink:

Up to 12 alarms

Operating

Temperature Range:

Relative Humidity:

10% to 85%

Dimensions:

155 mm x 38 mm

Weight:

227 g

Test Button:

Tests sensitivity, circuits, horn

5°C (40°F) to 38°C (100°F)

FOR FURTHER INFORMATION OR TECHNICAL ASSISTANCE CALL OR WRITE TO:

International Sales Office Dicon Safety Products P.O. Box 15 Cheltenham GL51 9UD

Tel: 01242 516241 Fax: 01242 222935 or call our Dicon Home Safety Helpline on 01242 251661

