


TO-126 (SOT-32) Plastic Package

C43C2

C43C2 PNP PLASTIC POWER TRANSISTOR

Complementary C42C series
General Purpose Applications



ABSOLUTE MAXIMUM RATINGS

Collector-emitter voltage ($V_{BE}=0$)
Collector-emitter voltage (open base)
Collector current
Total power dissipation up to $T_C = 25^\circ\text{C}$
Junction temperature
Collector-emitter saturation voltage
 $I_C = 1\text{ A}; I_B = 50\text{ mA}$
D.C. current gain
 $I_C = 200\text{ mA}; V_{CE} = 1\text{ V}$

V_{CES}	max.	40 V
V_{CEO}	max.	30 V
I_C	max.	3 A
P_D	max.	12.5 W
T_j	max.	150 °C
V_{CEsat}	max.	0.5 V
h_{FE}	min.	40
	max.	120

RATINGS (at $T_A=25^\circ\text{C}$ unless otherwise specified)

Limiting values

Collector-emitter voltage ($V_{BE}=0$)
Collector-emitter voltage (open base)
Emitter-base voltage (open collector)
Collector current (DC)

V_{CES}	max.	40 V
V_{CEO}	max.	30 V
V_{EBO}	max.	5.0 V
I_C	max.	3.0 A

C43C2

Collector current (Peak)*	I_{CM}	max.	5 A
Base current	I_B	max.	2 A
Total power dissipation up to $T_A = 25^\circ\text{C}$	P_D	max.	2.1 W
Total power dissipation up to $T_C = 25^\circ\text{C}$	P_D	max.	12.5 W
Junction temperature	T_j	max.	150 °C
Storage temperature	T_{stg}	-65 to +150 °C	

THERMAL RESISTANCE

From junction to case	$R_{th\ j-c}$	=	10 °C/W
From junction to ambient	$R_{th\ j-a}$	=	60 °C/W

CHARACTERISTICS

$T_C = 25^\circ\text{C}$ unless otherwise specified

Collector cutoff current $V_{BE} = 0$; $V_{CE} = \text{Rated } V_{CES}$	I_{CES}	max.	10 μA
Emitter cut-off current $I_C = 0$; $V_{EB} = 5\text{ V}$	I_{EBO}	max.	100 μA
Breakdown sus. voltage $I_C = 100\text{ mA}$; $I_B = 0$	$V_{CEO(sus)}^*$	min.	30 V
Saturation voltages $I_C = 1\text{ A}$; $I_B = 50\text{ mA}$	V_{CESat}^*	max.	0.5 V
$I_C = 1\text{ A}$; $I_B = 100\text{ mA}$	V_{BESat}^*	max.	1.3 V
D.C. current gain $I_C = 200\text{ mA}$; $V_{CE} = 1\text{ V}$	h_{FE}^*	min.	40
		max.	120
$I_C = 1\text{ A}$; $V_{CE} = 1\text{ V}$	h_{FE}^*	min.	20
Transition frequency $I_C = 20\text{ mA}$; $V_{CE} = 4\text{ V}$	f_T	typ.	40 MHz
Collector capacitance $V_{CB} = 10\text{ V}$; $I_E = 0$; $f = 1\text{ MHz}$	C_{cbo}	max.	125 pF

Switching time

Delay time + Rise time $I_C = 1\text{ A}$; $I_{B1} = I_{B2} = 0.1\text{ A}$	$t_d + t_r$	typ.	50 ns
---	-------------	------	-------

Storage time + Fall time

$V_{CC} = 30\text{ V}$; $t_p = 25\text{ }\mu\text{sec}$	t_s	typ.	500 ns
	t_f	typ.	50 ns

* Pulsed test: $P_W = 300\text{ ms}$; duty cycle = 2%.

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Discrete Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished on the CDIL Web Site/ CD is believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Discrete Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of
Continental Device India Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.
Telephone + 91-11-579 6150 Fax + 91-11-579 9569, 579 5290
e-mail sales@cdil.com www.cdil.com