ELWIS FLUORESCENT HANDLAMPS	,		
8 watt fluorescent handlamp fitted with	Voltage	Ref. No.	+48-850/si
electronic starter and ballast. IP67 rating	240 v, AC	19E008	7733767
and complies to BS4533. Resistant to oil	110 v AC	19E110	
and petrol. Fitted with 6m of flexible cable.	24 v AC or DC	19E024	
EHB FLUORESCENT HANDLAMPS (all fitted	with cable and chok	e unless stated)	
SINGLE TUBE HANDLAMP		Ref. No.	
Weatherproof	Voltage 240v	R54	
8 watt/360 lumens. Double insulated IP54	110v	R53	
protection. Handle is neoprene with polycarbonate	50v	K55	
outer tube. Choke housed in neoprene. Cable length	24v	K52	
is 58 metres.			
Immersion Proof	240v	WH1082	
8 watt/360 lumens, as weatherproof unit but with	110v	WH1081	
the lamp protected to IP67. Will work at depth of	50v	WH1085	
100 metres. Temps of -10°C to 60°C.	24v	WH1084	
Transformers available on request			
TWIN TUBE HANDLAMP	240v	R57	
Weatherproof 16 watt/720 lumens. Double insulated IP54	240V 110v	R56	
protection. Handle is neoprene with polycarbonate	710V 50v	M55	
outer tube. Choke housed in neoprene. Cable length	24v	M52	
is 5.8 metres.	_,,,		
Immersion Proof	240v	WH2082	
16 watt/720 lumens as weatherproof unit but with	110v	WH2081	
the lamp protected to IP67. Will work at depth of	50v	WH2085	
100 metres, temps of -10°C to 60°C.	24v	WH2084	
Transformers available on request			
BARREL HANDLAMP - Weatherproof	240v	R52	
8 watt/360 lumens. Double insulated IP54	110v	R51	
protection. Handle is neoprene with polycarbonate	50v	L55	
outer tube. Choke housed in neoprene. Cable length	24v	L52	
is 5.8 metres. Lamp length - 1000mm, diam 25mm.	•		
Transformers available on request			
CASK HANDLAMP - Weatherproof	240v	LH1082	
8 watt/360 lumens. Double insulated IP54	110v	LH1081	
protection. Handle is neoprene with polycarbonate	50v	LH1085	
outer tube. Choke housed in neoprene. Cable length	24v	LH1084	
is 5.8 metres. Lamp length - 480mm, diam 25mm.			
Transformers available on request			6 3
D.C. OPERATED HANDLAMP - Weatherproof	12v	R12	
8 watt/360 lumens. IP54 protection. Neoprene handle.	24v	R24	
Polycarbonate outer tube. Cable length is 6 metres.			
BRITICENT FLUORESCENT HANDLAMPS			
20 watt			A
1	Voltage 240v	Ref. No. EHL20	
Electronic IP67 Fluorescent 20 watt double insulated handlamp for 240 volt operation.	24UV	EMLZU	
Polycarbonate 54mm outer tube with rubber			
handle. Complete with 20 watt plc tube and 5			
metres cable.			
36 watt			
IP65 Fluorescent double insulated 36 watt	24v AC	6336/24	
handlamp. Polycarbonate outer tube. Complete with	110v AC	6336/110	
integral ballast and 5 metres cable. Length 800mm,	240v AC	6336/240	
Statileter Oshini			