

BDF7531 SERIES

DC FAN

Operating Temp. Range : -20 - +

Locked Rotor & Polarity Protection

Bearing : Ball Bearing

Housing : Plastic

Fan Blade : Plastic



75 x 75 x 30 mm

Type	Model	Rated Voltage VDC	Operate Voltage VDC	Rated Current mA	Rated Input W	Rated Speed rpm	Max Air flow m ³ /min.	CFM	Max Static Pressure mmAq	inchAq	Noise Level dB(A) / m	Weight gr
Middle Speed	* BDF7531-12MB	12	10.2 - 13.8	140	1.68	2200	0.24	8.5	4.8	0.19	33	100
	* BDF7531-24MB	24	20.4 - 27.6	90	2.16							
High Speed	* BDF7531-12HB	12	10.2 - 13.8	220	2.64	2600	0.30	10.6	9.2	0.36	38	100
	* BDF7531-24HB	24	20.4 - 27.6	110	2.64							
Top Speed	* BDF7531-12HHB	12	10.2 - 13.8	400	4.80	2900	0.33	11.6	12.5	0.50	43	100
	* BDF7531-24HHB	24	20.4 - 27.6	230	5.52							

* Approvals = UL / CLR (UL FOR CANADA) / TUV

