

LOC	DIST	REVISIONS					
AD	00	P	LYR	DESCRIPTION	DATE	DWN	APVD
			O	RELEASED	21JUN00	RB	KW
			A	REV PER OG3C-0377-00	15SEP00	RB	KW
			B	REV PER OG3C-0440-00	23OCT00	DB	KW

1 PACKAGE: TAPE AND REEL PER EIA-481 SPECIFICATIONS.
SEE TABLE FOR TAPE WIDTHS

2 MATERIAL: HOUSING AND PICK & PLACE CAP; HIGH TEMPERATURE
THERMOPLASTIC, COLOR - BLACK
CONTACTS; BRASS
HOLD-DOWNS; BERYLLIUM COPPER

3 FINISH: CONTACTS; 0.00254[.0001] BRIGHT TIN-LEAD
OVER 0.00127[.00005] NICKEL
HOLD-DOWNS; 0.00381[.00015] MATTE TIN-LEAD
OVER 0.00127[.00005] NICKEL

4 CIRCUIT POSITION #1 IDENTIFICATION MARK

5 DATUMS AND BASIC DIMENSIONS ARE ESTABLISHED BY CUSTOMER

6 RECOMMENDED PC BOARD THICKNESS OF 1.57[.062]

7 USE 1.510±0.025[.0595±.0010] DRILLED HOLE (#53 DRILL).
FINISH TO BE TIN-LEAD OVER 0.02[.0008] MIN COPPER

