

FEATURES


- Function, Pinout and Drive Compatible with the FCT and F Logic
- FCT-C speed at 6.2ns max. (Com'I)
FCT-A speed at 7.8ns max. (Com'I)
- Reduced V_{OH} (typically = 3.3V) versions of Equivalent FCT functions
- Edge-rate Control Circuitry for Significantly Improved Noise Characteristics
- Power-off disable feature
- Matched Rise and Fall times
- Fully Compatible with TTL Input and Output Logic Levels
- 64 mA Sink Current (Com'I), 32 mA (Mil)
15 mA Source Current (Com'I), 12 mA (Mil)
- 3-State Outputs

DESCRIPTION


The 'FCT191T is a reversible modulo-16 binary counter, featuring synchronous counting and asynchronous presetting. The preset allows the 'FCT191T to be used in programmable dividers. The count enable input, terminal

count output and ripple clock output make possible a variety of methods of implementing multiusage counters. In the counting modes, state changes are initiated by the rising edge of the clock.

FUNCTIONAL BLOCK DIAGRAM



PIN CONFIGURATIONS



DEFINITION OF FUNCTIONAL TERMS

Pin Names	Description
$\overline{CE}$	Count Enable Input (Active LOW)
CP	Clock Pulse Input (Active Rising Edge)
P ₀₋₃	Parallel Data Inputs
$\overline{PL}$	Asynchronous Parallel Load Input (Active LOW)
$\overline{U/D}$	Up/Down Count Control Input
Q ₀₋₃	Flip-Flop Outputs
$\overline{RC}$	Ripple Clock Output (Active LOW)
TC	Terminal Count Output (Active HIGH)

1716 Tbl 01

RC FUNCTION TABLE⁽²⁾

Inputs		Outputs	
$\overline{CE}$	CP	TC ⁽¹⁾	$\overline{RC}$
L		H	
H	X	X	H
X	X	L	H

1716 Tbl 02

MODE SELECT FUNCTION TABLE⁽²⁾

Inputs				Mode
$\overline{PL}$	$\overline{CE}$	$\overline{U/D}$	CP	
H	L	L		Count Up
H	L	H		Count Down
L	X	X	X	Preset (Asynchronous)
H	H	X	X	No Change (Hold)

1716 Tbl 03

Notes:

- TC is generated internally.
- H = HIGH Voltage Level. L = LOW Voltage Level. X = Don't Care, = LOW-to-HIGH clock transition.

ABSOLUTE MAXIMUM RATINGS^{1,2}

Symbol	Parameter	Value	Unit
T _{STG}	Storage Temperature	-65 to +150	°C
T _A	Ambient Temperature Under Bias	-65 to +135	°C
V _{CC}	V _{CC} Potential to Ground	-0.5 to +7.0	V
P _T	Power Dissipation	0.5	W

Notes: 1716 Tbl 04

1. Operation beyond the limits set forth in the above table may impair the useful life of the device. Unless otherwise noted, these limits are over the operating free-air temperature range.

Symbol	Parameter	Value	Unit
I _{OUTPUT}	Current Applied to Output	120	mA
V _{IN}	Input Voltage	-0.5 to +7.0	V
V _{OUT}	Voltage Applied to Output	-0.5 to +7.0	V

1716 Tbl 05

2. Unused inputs must always be connected to an appropriate logic voltage level, preferably either V_{CC} or ground.

RECOMMENDED OPERATING CONDITIONS

Free Air Ambient Temperature	Min	Max
Military	-55°C	+125°C
Commercial	0°C	+70°C

1716 Tbl 06

Supply Voltage (V _{CC})	Min	Max
Military	+4.5V	+5.5V
Commercial	+4.75V	+5.25V

1716 Tbl 07

DC ELECTRICAL CHARACTERISTICS (Over recommended operating conditions)

Symbol	Parameter		Min	Typ ¹	Max	Units	V _{CC}	Conditions
V _{IH}	Input HIGH Voltage		2.0			V		
V _{IL}	Input LOW Voltage				0.8	V		
V _H	Hysteresis			0.2		V		All inputs
V _{IK}	Input Clamp Diode Voltage			-0.7	-1.2	V	MIN	I _{IN} = -18mA
V _{OH}	Output HIGH Voltage	Military	2.4	3.3		V	MIN	I _{OH} = -12mA
		Commercial	2.4	3.3		V	MIN	I _{OH} = -15mA
V _{OL}	Output LOW Voltage	Military Commercial Commercial		0.3	0.5	V	MIN	I _{OL} = 32mA
				0.3	0.5	V	MIN	I _{OL} = 48mA
				0.3	0.5	V	MIN	I _{OL} = 64mA
I _I	Input HIGH Current				20	μA	MAX	V _{IN} = V _{CC}
I _{IH}	Input HIGH Current				5	μA	MAX	V _{IN} = 2.7V
I _{IL}	Input LOW Current				-5	μA	MAX	V _{IN} = 0.5V
I _{OS}	Output Short Circuit Current ²		-60	-120	-225	mA	MAX	V _{OUT} = 0.0V
I _{OFF}	Power-off Disable				100	μA	0V	V _{OUT} = 4.5V
C _{IN}	Input Capacitance ³			5	10	pF	MAX	All inputs
C _{OUT}	Output Capacitance ³			9	12	pF	MAX	All outputs
I _{CC}	Quiescent Power Supply Current			0.2	1.5	mA	MAX	V _{IN} ≤ 0.2V, V _{IN} ≥ V _{CC} - 0.2V

1716 Tbl 08

Notes:

1. Typical values are at V_{CC} = 5.0V, T_A = +25°C ambient.
2. Not more than one output should be shorted at a time. Duration of short should not exceed one second. The use of high speed test apparatus and/or sample and hold techniques are preferable in order to minimize internal chip heating and more accurately reflect

operational values. Otherwise prolonged shorting of a high output may raise the chip temperature well above normal and thereby cause invalid readings in other parameter tests. In any sequence of parameter tests, I_{OS} tests should be performed last.

3. This parameter is guaranteed but not tested.

DC CHARACTERISTICS (Over recommended operating conditions unless otherwise specified.)

Symbol	Parameter	Typ ¹	Max	Units	Conditions
ΔI_{CC}	Quiescent Power Supply Current (TTL inputs HIGH) ²	0.5	2.0	mA	$V_{CC} = \text{MAX}$, $V_{IN} = 3.4V^2$, $f_1 = 0$, Outputs Open
I_{CCD}	Dynamic Power Supply Current ³	0.15	0.25	mA/ MHz	$V_{CC} = \text{MAX}$, One Bit Toggling, Preset Mode, 50% Duty Cycle, Outputs Open, $\overline{MR} = V_{CC} = \overline{SR}$, $\overline{PL} = \overline{CE} = \overline{U/D} = CP = \text{GND}$, $V_{IN} \leq 0.2V$ or $V_{IN} \geq V_{CC} - 0.2V$
I_C	Total Power Supply Current ⁵	1.0	2.8	mA	$V_{CC} = \text{MAX}$, Preset Mode, 50% Duty Cycle, Outputs Open, One Bit Toggling at $f_1 = 5\text{MHz}$, $\overline{PL} = \overline{CE} = \overline{U/D} = CP = \text{GND}$, $V_{IN} = V_{CC}$, $V_{IN} = \text{GND}$
		1.2	3.8	mA	$V_{CC} = \text{MAX}$, Preset Mode, 50% Duty Cycle, Outputs Open, One Bit Toggling at $f_1 = 5\text{MHz}$, $\overline{PL} = \overline{CE} = \overline{U/D} = CP = \text{GND}$, $V_{IN} = 3.4V$, $V_{IN} = \text{GND}$
		3.2	6.5 ⁴	mA	$V_{CC} = \text{MAX}$, Preset Mode, 50% Duty Cycle, Outputs Open, Four Bits Toggling at $f_1 = 5\text{MHz}$, $\overline{PL} = \overline{CE} = \overline{U/D} = CP = \text{GND}$, $V_{IN} = V_{CC}$, $V_{IN} = \text{GND}$,
		4.2	10.5 ⁴	mA	$V_{CC} = \text{MAX}$, Preset Mode, 50% Duty Cycle, Outputs Open, Four Bits Toggling at $f_1 = 5\text{MHz}$, $\overline{PL} = \overline{CE} = \overline{U/D} = CP = \text{GND}$, $V_{IN} = 3.4V$ or $V_{IN} = \text{GND}$

1716 Tbl 09

Notes:

- Typical values are at $V_{CC} = 5.0V$, +25°C ambient.
- Per TTL driven input ($V_{IN} = 3.4V$); all other inputs at V_{CC} or GND.
- This parameter is not directly testable, but is derived for use in Total Power Supply calculations.
- Values for these conditions are examples of the I_{CC} formula. These limits are guaranteed but not tested.
- $I_C = I_{\text{QUIESCENT}} + I_{\text{INPUTS}} + I_{\text{DYNAMIC}}$
 $I_C = I_{CC} + \Delta I_{CC} D_H N_i + I_{CCD} (f_0/2 + f_1 N_i)$
 I_{CC} = Quiescent Current with CMOS input levels
 ΔI_{CC} = Power Supply Current for a TTL High Input ($V_{IN} = 3.4V$)

D_H = Duty Cycle for TTL Inputs High
 N_i = Number of TTL Inputs at D_H
 I_{CCD} = Dynamic Current Caused by an Input Transition Pair (HLH or LHL)
 f_0 = Clock Frequency for Register Devices (Zero for Non-Register Devices)
 f_1 = Input Frequency
 N_i = Number of Inputs at f_1
 All currents are in milliamps and all frequencies are in megahertz.

SWITCHING CHARACTERISTICS OVER OPERATING RANGE

Sym.	Parameter	Test Condition ¹	'FCT191T				'FCT191AT				'FCT191CT				Units
			MIL		COM'L		MIL		COM'L		MIL		COM'L		
			Min. ²	Max.	Min. ²	Max.	Min. ²	Max.	Min. ²	Max.	Min. ²	Max.	Min. ²	Max.	
t _{PLH} t _{PHL}	Propagation Delay CP to Q _n	C _L = 50pF R _L = 500Ω	1.5	16.0	2.5	12.0	1.5	10.5	2.5	7.8	1.5	8.4	1.5	6.2	ns
t _{PLH} t _{PHL}	Propagation Delay CP to TC		2.0	16.0	3.0	14.0	2.0	12.2	3.0	11.8	1.5	9.8	1.5	9.4	ns
t _{PLH} t _{PHL}	Propagation Delay CP to RC		1.5	12.5	2.5	8.5	1.5	10.0	2.5	8.5	1.5	7.9	1.5	6.8	ns
t _{PLH} t _{PHL}	Propagation Delay CE to RC		2.0	8.5	2.0	8.0	2.0	8.0	2.0	7.2	1.5	6.4	1.5	6.0	ns
t _{PLH} t _{PHL}	Propagation Delay U/D to RC		4.0	22.5	4.0	20.0	4.0	14.7	4.0	13.0	2.5	11.7	2.5	11.0	ns
t _{PLH} t _{PHL}	Propagation Delay U/D to TC		3.0	13.0	3.0	11.0	3.0	8.5	3.0	7.2	1.5	6.8	1.5	6.1	ns
t _{PLH} t _{PHL}	Propagation Delay P _n to Q _n		1.5	16.0	2.0	14.0	1.5	10.4	2.0	9.1	1.5	8.3	1.5	7.7	ns
t _{PLH} t _{PHL}	Propagation Delay PL to Q _n		3.0	14.0	3.0	13.0	3.0	9.1	3.0	8.5	2.0	7.3	2.0	7.2	ns
t _{SU}	Set-up Time, HIGH or LOW P _n to PL		6.0		5.0		5.0		4.0		4.0		3.5		
t _H	Hold Time, HIGH or LOW P _n to PL		1.5		1.5		1.5		1.5		1.5		1.0		ns
t _{SU}	Set-up Time LOW CE to CP		10.5		10.0		9.5		9.0		7.6		7.2		ns
t _H	Hold Time LOW CE to CP		0		0		0		0		0		0		ns
t _{SU}	Set-up Time, HIGH or LOW U/D to CP		12.0		12.0		10.0		10.0		8.5		8.0		ns
t _H	Hold Time, HIGH or LOW U/D to CP		0		0		0		0		0		0		ns
t _W	PL Pulse Width LOW		8.5		6.0		8.0		5.5		6.0		5.0		ns
t _W	Clock Pulse Width HIGH or LOW	7.0		5.0		6.0		4.0 ³		5.0		4.0 ³		ns	
t _{REM}	Recovery Time PL to CP	7.5		6.0		6.5		5.0		5.0		4.5		ns	

Notes:

- See test circuit and waveforms.
- Minimum limits are guaranteed but not tested on Propagation Delays.
- These parameters are guaranteed but not tested.

1716 Tbl 10

ORDERING INFORMATION

<u>CYxxFCT</u> Temp. Class	<u>xxxx</u> Device type	<u>x</u> Package	<u>x</u> Processing	
				C Commercial
				M Military Temperature
				MB MIL-STD-883, Class B
				P Plastic DIP
				D CERDIP
				SO Small Outline IC
				L Leadless Chip Carrier
				Q QSOP
				191T Up/Down Binary Counter
				191AT Fast Up/Down Binary Counter
				191CT Ultra Fast Up/Down Binary Counter
				74 Commercial
				54 Military

1716 03