

STANDARD KEYBOARD

104/105-Key Keyboard

FKB8729 SERIES



■ FEATURES

- Compatible with PC99 specifications (PS/2 connector)
- Supports Windows® keyboard functions
- Excellent operation
 - Curved keyswitch panel
 - Full-travel 3.8 mm (0.149 in.) keystroke, 55 g operating force (1.936 oz.), 20 g (0.704 oz.) tactile response
 - Soft tactile feedback, ultra silent
- High quality and reliability
- Laser printed keycaps meet environmental requirements
- Overall light gray color

■ MAIN APPLICATIONS

- Desktop-type personal computer
- Workstation

FKB8729 SERIES

■ SPECIFICATIONS

Item		Specification
		FKB8729 Series
Mechanical	Number of Keys	(1) U.S. : 104 keys (2) Europe: 105 keys
	Key Switch Type	Membrane switch
	Keytop	Rectangular cylindrical, Curved sculptured
	Operating Force	55 gf \pm 25 gf (1.936 \pm 0.88 oz.)
	Stroke	3.8 mm \pm 0.5 mm (0.149 \pm 0.019)
	Tactile	20 gf typ. (0.704 oz.), Soft
	Operating Life	10 M operations min.
	Tilt	2 levels
Electrical	Power Supply	+5 V \pm 0.25 V DC, 100 mA max.
	Interface	Serial transmission (clock synchronous type) PC99 compatible
	Interlock	F-key rollover
	Connector	Mini-DIN 6 pin (PS/2 type)
Environment	Operating Temperature	+10 to 50°C
	Storage Temperature	-10 to 60°C
	Humidity	90% RH max. at +40°C max. inversely proportional change to 50% RH at 60°C

FKB8729 SERIES

■ PART NUMBERS


Part Number	Number of Keys	Key Arrangement	Connector	Notes
FKB8729-601	104	US	PS/2, 6-pin MiniDIN	PC99, No Logo
FKB8729-651				PC99, Fujitsu Logo
FKB8729-602	105	U.K.		PC99, No Logo
FKB8729-603		German		
FKB8729-604		French		
FKB8729-605		Italian		
FKB8729-606		Spanish		
FKB8729-607		Swedish		
FKB8729-608		Swiss		

To Be Discontinued

FKB8729 SERIES


■ CONNECTOR PIN ASSIGNMENT

Mini-DIN 6 pin




Pin number	Signal name
1	Data
2	—
3	GND (SG)
4	+5 V
5	Clock
6	—
SHELL	GND (FG)

■ OPERATING FORCE AND TRAVEL CHARACTERISTICS




FKB8729 SERIES

■ DIMENSIONS




■ KEY LAYOUT

U.S.




U.K.




FKB8729 SERIES


German



French




Italian




FKB8729 SERIES


Spanish



Swedish



Swiss



Fujitsu Components International Headquarter Offices

Japan

Fujitsu Component Limited
Gotanda-Chuo Building
3-5, Higashigotanda 2-chome, Shinagawa-ku
Tokyo 141, Japan
Tel: (81-3) 5449-7010
Fax: (81-3) 5449-2626
Email: promothq@ft.ed.fujitsu.com
Web: www.fcl.fujitsu.com

North and South America

Fujitsu Components America, Inc.
250 E. Caribbean Drive
Sunnyvale, CA 94089 U.S.A.
Tel: (1-408) 745-4900
Fax: (1-408) 745-4970
Email: components@us.fujitsu.com
Web: <http://www.fujitsu.com/us/services/edevices/components/>

Europe

Fujitsu Components Europe B.V.
Diamantlaan 25
2132 WV Hoofddorp
Netherlands
Tel: (31-23) 5560910
Fax: (31-23) 5560950
Email: info@fceu.fujitsu.com
Web: emea.fujitsu.com/components/

Asia Pacific

Fujitsu Components Asia Ltd.
102E Pasir Panjang Road
#01-01 Citilink Warehouse Complex
Singapore 118529
Tel: (65) 6375-8560
Fax: (65) 6273-3021
Email: fcal@fcal.fujitsu.com
Web: <http://www.fujitsu.com/sg/services/micro/components/>

©2006 Fujitsu Components America, Inc. All rights reserved. All trademarks or registered trademarks are the property of their respective owners.

Fujitsu Components America or its affiliates do not warrant that the content of datasheet is error free. In a continuing effort to improve our products Fujitsu Components America, Inc. or its affiliates reserve the right to change specifications/datasheets without prior notice.
Rev. June7/2006

To Be Discontinued