



APT PART NUMBER	DRAIN- SOURCE VOLTAGE BVDSS (VOLTS)	ON RESIS- TANCE RDS(ON) (OHMS)	DRAIN CURRENT		INPUT CAPAC- ITANCE CISS (pF)	POWER DISSI- PATION PD(MAX) (WATTS)	NOTES	CASE STYLE AND DEVICE TYPE
			ID (CONT) (AMPS)	IDM (PULSED) (AMPS)				
APT1001RAN	1000	1.00	9.5	38.0	2450	230	1	TO-3 (TO-204AA)
APT1001R2AN	1000	1.20	9.0	36.0	2450	230	1	
APT1002RAN	1000	2.00	6.0	24.0	1750	198	1	
APT1002R4AN	1000	2.40	5.5	22.0	1750	198	1	
APT1003R5AN	1000	3.50	4.0	16.0	880	150	1	
APT1004R2AN	1000	4.20	3.5	14.0	880	150	1	
APT901RAN	900	1.00	9.5	38.0	2450	230	1	
APT901R2AN	900	1.20	9.0	36.0	2450	230	1	
APT902RAN	900	2.00	6.0	24.0	1750	198	1	HERMETIC COMMERCIAL AND HI-REL MILITARY N-CHANNEL MOSFET
APT902R4AN	900	2.40	5.5	22.0	1750	198	1	
APT903R5AN	900	3.50	4.0	16.0	880	150	1	
APT904R2AN	900	4.20	3.5	14.0	880	150	1	
APT8075AN	800	0.75	11.0	44.0	2450	230	1	
APT8090AN	800	0.90	10.0	40.0	2450	230	1	
APT801R2AN	800	1.20	8.0	32.0	1750	198	1	
APT801R4AN	800	1.40	7.5	30.0	1750	198	1	
APT802RAN	800	2.00	5.5	22.0	880	150	1	
APT802R4AN	800	2.40	5.0	20.0	880	150	1	
APT7575AN	750	0.75	11.0	44.0	2450	230	1	
APT7590AN	750	0.90	10.0	40.0	2450	230	1	
APT751R2AN	750	1.20	8.0	32.0	1750	198	1	
APT751R4AN	750	1.40	7.5	30.0	1750	198	1	
APT752RAN	750	2.00	5.5	22.0	880	150	1	
APT752R4AN	750	2.40	5.0	20.0	880	150	1	
APT6040AN	600	0.40	15.5	62.0	2400	230	1	
APT6045AN	600	0.45	14.5	58.0	2400	230	1	
APT6060AN	600	0.60	11.5	46.0	1700	198	1	
APT6070AN	600	0.70	10.5	42.0	1700	198	1	
APT601R2AN	600	1.20	7.0	28.0	850	150	1	
APT601R6AN	600	1.60	6.0	24.0	850	150	1	
APT5540AN	550	0.40	15.5	62.0	2400	230	1	
APT5545AN	550	0.45	14.5	58.0	2400	230	1	
APT5560AN	550	0.60	11.5	46.0	1700	198	1	
APT5570AN	550	0.70	10.5	42.0	1700	198	1	
APT551R2AN	550	1.20	7.0	28.0	850	150	1	
APT551R6AN	550	1.60	6.0	24.0	850	150	1	
APT5025AN	500	0.25	20.0	80.0	2400	230	1	
APT5030AN	500	0.30	18.0	72.0	2400	230	1	
APT5040AN	500	0.40	14.5	58.0	1700	198	1	
APT5050AN	500	0.50	13.0	52.0	1700	198	1	
APT5085AN	500	0.85	8.5	34.0	850	150	1	
APT501R1AN	500	1.10	7.5	30.0	850	150	1	
APT4525AN	450	0.25	20.0	80.0	2400	230	1	
APT4530AN	450	0.30	18.0	72.0	2400	230	1	
APT4540AN	450	0.40	14.5	58.0	1700	198	1	
APT4550AN	450	0.50	13.0	52.0	1700	198	1	
APT4585AN	450	0.85	8.5	34.0	850	150	1	
APT451R1AN	450	1.10	7.5	30.0	850	150	1	
APT4020AN	400	0.20	22.5	90.0	2400	230	1	
APT4025AN	400	0.25	20.0	80.0	2400	230	1	
APT4030AN	400	0.30	17.0	68.0	1700	198	1	
APT4040AN	400	0.40	14.5	58.0	1700	198	1	
APT4055AN	400	0.55	10.5	42.0	850	150	1	
APT4080AN	400	0.80	8.5	34.0	850	150	1	
APT3520AN	350	0.20	22.5	90.0	2400	230	1	
APT3525AN	350	0.25	20.0	80.0	2400	230	1	
APT3530AN	350	0.30	17.0	68.0	1700	198	1	
APT3540AN	350	0.40	14.5	58.0	1700	198	1	
APT3555AN	350	0.55	10.5	42.0	850	150	1	
APT3580AN	350	0.80	8.5	34.0	850	150	1	

NOTE 1. - CURRENTLY AVAILABLE