

TP-1610 16 E1/T1 cPCI VoIP Communication Board



- High channel density
- Concurrent toll quality voice and fax support
- Carrier grade applications
- Reduced system cost and increased reliability
- Fast time-to-market
- Flexible and easy migration to VoIP Networks
- Extensive VoIP experience

The **TP-1610** cPCI VoIP communication board, based on dual AudioCodes' TPM-1100 PMC Modules, is an ideal building block for deploying high-density, high availability Voice over IP (VoIP) systems. The TP-1610 is suitable for VoIP gateways, IP-enabled call centers, large Telcos and next generation DLCs. Offering integrated voice gateway functionality capable of delivering up to 480 simultaneous calls, the TP-1610 supports all necessary functions for voice and fax streaming over IP networks.

DELIVER FEATURE-RICH SOLUTION

The TP-1610 supports a broad selection of voice processing related algorithms, including G.711, G.723.1 and G.729A Vocoders, G.168-compliant echo cancellation, T.38 Real-time Fax over IP, a wide selection of In-band and Out-band tone detection and generation as well as signaling protocols support including ISDN PRI, SIGTRAN (M2UA, IUA) and CAS.

COMPLY WITH INDUSTRY STANDARDS

The TP-1610 board complies with industry standard network control protocols including MGCP, MEGACO (H.248), SIP, H.323 or AudioCodes' proprietary TPNC. These allow for the implementation of a distributed gateway architecture that separates call processing functions from media streaming functions, resulting in better redundancy, scalability and higher system availability.

PROTECT CUSTOMER INVESTMENT

The TP-1610 is a member of AudioCodes' 4th generation of the widely deployed TrunkPack® Media Gateway on a blade family. Like the other members of the TrunkPack® family, the TP-1610 supports AudioCodes API, which enables software download, provisioning and control. Maintaining essential API backward compatibility of future releases in order to protect customers' investment, is an important feature of AudioCodes' software update/upgrade program.

ENABLE FAST & EASY INTEGRATION

Enabling accelerated design cycles with high density and reduced costs, the TP-1610 is an ideal building block for scalable, reliable VoIP solutions. With the TP-1610's comprehensive feature set, customers can quickly design a wide range of solutions for migration to VoIP networks.

TP-1610 FEATURES

- Up to 480 voice/fax independent multiple LBR channels
- VoIP packet streaming (RTP/ RTCP) per RFC 1889/1890
- Standard control: MGCP (RFC 2705), MEGACO (H.248), SIP/H.323
- Real-time Fax over IP/T.38
- On-board announcement support towards PSTN/TDM and IP
- Tone detection and generation (MF, DTMF, RFC 2833)
- PSTN Signaling: CAS, ISDN PRI, V5.2 (AN), and SS7
- SIGTRAN IUA, M2UA, M3UA over SCTP
- cPSB PICMG 2.16 compliant Ethernet on the backplane

TP-1610

SPECIFICATIONS

Software Specifications	
Capacity	60, 120, 240 or 480 independent digital voice, fax and data ports
Voice Compression	G.711, G.723.1, G.729A, G.726/G.727, NetCoder® Additional coders supported - contact AudioCodes for further information
Echo Cancellation	G.168 compliant 32, 64*, 128* msec echo tail
Gain Control	Programmable
Fax Relay	Real-time fax over IP/T.38 compliant, automatic fallback to G.711
In-band/Out-band Signaling	Packet side or PSTN side, DTMF and tone detection and generation
IVR Support	On-board announcement storage - 10 Mb Recorded prompts - 20 minutes of G.711, 200 minutes of G.723
VoIP Standards Compliance	RTP/RTCP per RFC 1889/1890 DTMF over RTP per RFC 2833
Control Protocols	Media Gateway on a blade mode: <ul style="list-style-type: none"> Controlled by either MGCP or MEGACO PCI used for power only SIP, H.323 TPNCP - AudioCodes' proprietary VoIP API Library
Management Interfaces	SNMP V2: Standard MIB-2, RTP MIB, Trunk MIB, AudioCodes proprietary MIB On-board Embedded Web Server
Operating System	<ul style="list-style-type: none"> Windows NT, 2000, XP Linux Solaris on Intel/Sparc
Signaling	
PSTN	CAS T1 robbed bit, MFC/R2 numerous country variants CCS ISDN PRI: numerous country variants including ETSI EURO ISDN, ANSI NI2, DMS, 5ESS, Japan INS1500 V5.2 AN (Contact AudioCodes)
SIGTRAN	IUA over SCTP per RFC 3057/2960 SS7 MTP2 link termination M2UA and M3UA over SCTP
Hardware Specifications	
Ethernet	Dual redundant 100 Base-T ports
Hot Swap	Full hot swap supported per PICMG 2.1
Physical Interfaces	Form factor - 6U PICMG 2.0 single cPCI slot TDM Interface - H.110 CT Bus Telephony - two 50-pin Telco connectors on rear panel Ethernet - cPSB PICMG 2.16 on the backplane, Dual RJ-45 on rear panel
Power	40.7W, 3A at 5V, 7.8A at 3.3V

* With reduced channel capacity

APPLICATIONS

- Next Generation Switches
- IP Services Platforms
- VoIP Access Gateways
- Trunking Gateways
- Cable Telephony Gateways
- IP Enabled Call Centers

ABOUT AUDIOCODES

AudioCodes Ltd. (NASDAQ: AUDC) designs, develops and markets Voice over Packet media gateway technologies and systems for converged networks. The company is a market leader in voice compression technology and the key originator of the ITU G.723.1 standard for the emerging Voice over IP market. AudioCodes' product line includes enabling technology products such as Voice over Packet chip processors, VoIP communication boards, VoIP media gateway modules and CPE devices. In addition, AudioCodes provides OEMs with media gateway system solutions for packet networks in the wireline, wireless, broadband access and media server markets.

International Headquarters

4 HaHoresh Street
Yehud, Israel 56470
Tel: +972-3-539-4000
Fax: +972-3-539-4040

US Headquarters

2890 Zanker Road, Suite 200
San Jose, CA 95134
Tel: +1-408-577-0488
Fax: +1-408-577-0492

China

Room 209, Tower A, Grand Pacific Building
8A Guanghua Road
Chao Yang District
Beijing 100026, P. R. China
Tel: +86-10-6581-6622
Fax: +86-10-6581-5599

Japan

S Building B1F, 2-30-2
Chuo, Nakano-ku
Tokyo 164-0011, Japan
Tel/Fax: +81-3-5348-1405

E-Mail info@audiocodes.com

www.audiocodes.com

© 2003 AudioCodes Ltd. All rights reserved. AC, AudioCodes, AudioCodes logo, AudioCodes, IPmedia, Mediant, MediaPack, MP-MLQ, NetCoder, Stretto, TrunkPack and VoicePacketizer are trademarks or registered trademarks of AudioCodes Ltd. All other marks are the property of their respective owners. The information and specifications in this document and the product(s) are subject to change without notice.
Ref # LTRT-00220 01/03 V.5

