

Silicon PNP Power Transistors

2SB891F

DESCRIPTION


- With TO-126 package
- Complement to type 2SD1189F
- Low collector saturation voltage

APPLICATIONS

- For low frequency power amplifier applications

PINNING

PIN	DESCRIPTION
1	Emitter
2	Collector;connected to mounting base
3	Base

Absolute maximum ratings($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	Open emitter	-40	V
V_{CEO}	Collector-emitter voltage	Open base	-32	V
V_{EBO}	Emitter-base voltage	Open collector	-5	V
I_C	Collector current (DC)		-2	A
I_{CM}	Collector current-Peak		-3	A
P_C	Collector power dissipation	$T_a=25^\circ\text{C}$	1.2	W
		$T_C=25^\circ\text{C}$	5	
T_j	Junction temperature		150	$^\circ\text{C}$
T_{stg}	Storage temperature		-55~150	$^\circ\text{C}$

Silicon PNP Power Transistors

2SB891F

CHARACTERISTICS

Tj=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{(BR)CEO}$	Collector-emitter breakdown voltage	$I_C = -1\text{mA}$; $I_B = 0$	-32			V
$V_{(BR)CBO}$	Collector-base breakdown voltage	$I_C = -50\mu\text{A}$; $I_E = 0$	-40			V
$V_{(BR)EBO}$	Emitter-base breakdown voltage	$I_E = -50\mu\text{A}$; $I_C = 0$	-5			V
V_{CEsat}	Collector-emitter saturation voltage	$I_C = -2.0\text{A}$; $I_B = -0.2\text{A}$		-0.5	-0.8	V
I_{CBO}	Collector cut-off current	$V_{CB} = -20\text{V}$; $I_E = 0$			-1.0	μA
I_{EBO}	Emitter cut-off current	$V_{EB} = -4\text{V}$; $I_C = 0$			-1.0	μA
h_{FE}	DC current gain	$I_C = -0.5\text{A}$; $V_{CE} = -3\text{V}$	82		390	
f_T	Transition frequency	$I_C = -0.5\text{A}$; $V_{CE} = -5\text{V}$; $f = 30\text{MHz}$		100		MHz
C_{OB}	Collector output capacitance	$I_E = 0$; $f = 1\text{MHz}$; $V_{CB} = -10\text{V}$		50		pF

◆ h_{FE-2} Classifications

P	Q	R
82-180	120-270	180-390

Silicon PNP Power Transistors

2SB891F

PACKAGE OUTLINE




Fig.2 Outline dimensions