


Surface Mount, Molded, Shielded Inductor



FEATURES

- Molded construction provides superior strength and moisture resistance.
- Tape and reel packaging for automatic handling, 2000/reel, EIA 481.
- Compatible with vapor phase, infrared and wave soldering methods.
- Shielded construction minimizes coupling to other components.
- 100% Lead (Pb)-free and RoHS compliant


ELECTRICAL SPECIFICATIONS

Inductance Range: .01 μ H to 100 μ H.
Inductance Tolerance: \pm 20% for 0.01 μ H to 0.82 μ H. \pm 10% for 1.0 μ H to 100 μ H standard. 2%, 3% and 5% (also 1% on some values) tolerances available.
Temperature Range: - 55°C to + 125°C.
Coilform Material: Non-magnetic for 0.01 μ H to 0.10 μ H. Powdered Iron for 0.12 μ H to 100 μ H.

TEST EQUIPMENT

- H/P 4342A Q meter with Vishay Dale test fixture or equivalent.
- H/P 4191A RF Impedance Analyzer (for SRF measurements).
- Wheatstone Bridge.

STANDARD ELECTRICAL SPECIFICATIONS						
IND. (μ H)	TOL.	Q MIN.	TEST FREQ. L & Q (MHz)	SELF-RESONANT FREQ. MIN. (MHz)	DCR MAX. (Ohms)	RATED DC CURRENT (mA)
0.010	\pm 20%	50	50	1000	0.10	810
0.012	\pm 20%	50	50	1000	0.11	750
0.015	\pm 20%	50	50	1000	0.12	720
0.018	\pm 20%	50	50	1000	0.13	690
0.022	\pm 20%	45	50	1000	0.15	640
0.027	\pm 20%	45	50	1000	0.17	610
0.033	\pm 20%	45	50	1000	0.18	585
0.039	\pm 20%	40	50	1000	0.24	530
0.047	\pm 20%	40	50	1000	0.26	495
0.056	\pm 20%	40	50	1000	0.28	485
0.068	\pm 20%	40	50	1000	0.35	475
0.082	\pm 20%	38	50	900	0.45	460
0.10	\pm 20%	36	50	700	0.50	450
0.12	\pm 20%	40	25.2	500	0.20	630
0.15	\pm 20%	40	25.2	470	0.20	600
0.18	\pm 20%	40	25.2	400	0.24	580
0.22	\pm 20%	40	25.2	330	0.30	565
0.27	\pm 20%	40	25.2	310	0.33	500
0.33	\pm 20%	40	25.2	280	0.36	475
0.39	\pm 20%	40	25.2	230	0.40	465
0.47	\pm 20%	40	25.2	220	0.44	460
0.56	\pm 20%	40	25.2	200	0.46	455
0.68	\pm 20%	40	25.2	180	0.48	450
0.82	\pm 20%	40	25.2	160	0.50	450
1.0	\pm 10%	30	7.96	120	0.60	400
1.2	\pm 10%	30	7.96	110	0.65	390
1.5	\pm 10%	30	7.96	90.0	0.75	370
1.8	\pm 10%	30	7.96	85.0	0.85	350
2.2	\pm 10%	30	7.96	65.0	0.90	320
2.7	\pm 10%	30	7.96	60.0	1.00	290
3.3	\pm 10%	30	7.96	60.0	1.10	270
3.9	\pm 10%	30	7.96	58.0	1.20	250
4.7	\pm 10%	30	7.96	52.0	1.25	220
5.6	\pm 10%	30	7.96	50.0	1.40	210
6.8	\pm 10%	30	7.96	40.0	1.60	205
8.2	\pm 10%	30	7.96	35.0	1.65	195
10.0	\pm 10%	30	2.52	30.0	2.00	185
12.0	\pm 10%	30	2.52	24.0	2.30	175
15.0	\pm 10%	30	2.52	20.0	2.50	165
18.0	\pm 10%	30	2.52	17.0	2.70	155
22.0	\pm 10%	30	2.52	16.0	3.10	150
27.0	\pm 10%	30	2.52	14.5	3.30	125
33.0	\pm 10%	30	2.52	14.5	5.10	115
39.0	\pm 10%	30	2.52	14.0	5.90	105
47.0	\pm 10%	30	2.52	13.0	8.00	100
56.0	\pm 10%	30	2.52	11.5	10.0	95
68.0	\pm 10%	30	2.52	11.0	10.0	90
82.0	\pm 10%	30	2.52	11.0	11.0	85
100.0	\pm 10%	30	0.796	6.0	12.0	80



*Recommended minimum spacing between components.

PART MARKING	
— Dale	
— Inductance value	
— Date code	

DESCRIPTION				
ISC-1210 MODEL	10 μ H INDUCTANCE VALUE	\pm 10% INDUCTANCE TOLERANCE	ER PACKAGE CODE	e3 JEDEC LEAD FREE STANDARD
GLOBAL PART NUMBER				
I S C	1 2 1 0	E R	1 0 0	K
PRODUCT FAMILY	SIZE	PACKAGE CODE	INDUCTANCE VALUE	TOL.



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.