

Product Specifications

L4P43A-PDMDF-13M-X

LDF4-50A SureFlex™ Jumper with interface types 7-16 DIN Male and 7-16 DIN Female, 13 m



CHARACTERISTICS


General Specifications

Body Style, Connector A	Straight
Body Style, Connector B	Straight
Cable Family	LDF4-50A
Interface, Connector A	7-16 DIN Male
Interface, Connector B	7-16 DIN Female
Length	13.000 m 42.651 ft
Attachment, Connector B	Field attachment

Electrical Specifications

DTF, Connector A	-32.00 dB
------------------	-----------

Jumper Assembly Sample Label



Return Loss

Frequency Band	VSWR	Return Loss (dB)
800–970 MHz	1.15	23.13
1420–1530 MHz	1.15	23.13
1700–2180 MHz	1.15	23.13

INCLUDED PRODUCTS

Product Specifications

L4P43A-PDMDF-13M-X



LDF4-50A

LDF4-50A, HELIAX® Low Density Foam Coaxial Cable, corrugated copper, 1/2 in, black PE jacket



L4TDF-PS

7-16 DIN Female Positive Stop™ for 1/2 in LDF4-50A cable



L4TDF-PSA

7-16 DIN Female Positive Stop™ for 1/2 in AL4RPV-50, LDF4-50A cable
