



(2.00mm) .0787"

MPTC, MPSC SERIES

MPTC-01-80-01-6.30-01-L-V-LC

MPSC-01-80-01-7.70-01-L-V

25A SIGNAL POWER COMBO SYSTEM

MPTC Mates with:
MPSC
MPSC Mates with:
MPTC

SPECIFICATIONS

For complete specifications see www.samtec.com?MPTC or www.samtec.com?MPSC

Insulator Material: Black LCP

Terminal Material: Copper Alloy

Plating:

Sn or Au over 50µ" (1.27µm) Ni

Current Rating:

Testing Now!

Operating Temp Range: -55°C to +105°C

Voltage Rating: 300 VAC/424 VDC


RoHS Compliant:

Yes

Lead-Free Solderable:

Yes

MATED HEIGHT



APPLICATION SPECIFIC OPTION

- Asymmetric power pin placement.
 - 4, 8, 16, 36 and 48 total signal pins
 - Solder leads for (2,36mm) .093" thick board.
- Call Samtec.

ALSO AVAILABLE

- Right Angle. See MPTC-RA Series.

Note: Some sizes, styles and options are non-standard, non-returnable.

MPTC	PWR PINS	SIG PINS	PWR PINS	LEAD STYLE	01	PLATING OPTION	V	OTHER OPTION
	-01, -02 = Power Pins Per End	-24 = Total Signal Pins -80 = Total Signal Pins	-01, -02 = Power Pins Per End	-6.30 = (6,30mm) 0.248"		-L = 10µ" (0,25µm) Gold on contact, Matte Tin on tail (Power & Signal) -T = Matte Tin on contacts and tail (Power), Gold on contact, Matte Tin on tail (Signal)		-LC = Locking Clip (Manual placement required)

POWER PINS/END	A
-01	(59,44) 2.340
-02	(69,44) 2.734



MPSC	PWR PINS	SIG PINS	PWR PINS	LEAD STYLE	01	PLATING OPTION	V	OTHER OPTION
	-01, -02 = Power Pins Per End	-24 = Total Signal Pins -80 = Total Signal Pins	-01, -02 = Power Pins Per End	-7.70 = (7,70mm) .303"		-L = 10µ" (0,25µm) Gold on contact, Matte Tin on tail (Power & Signal) -T = Matte Tin on contacts and tail (Power), Gold on contact, Matte Tin on tail (Signal)		-LC = Locking Clip (Manual placement required)

POWER PINS/END	A
-01	(59,44) 2.340
-02	(69,44) 2.734

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM