


Features

- 0 dBm Output Level at 5800 MHz
- Channel Step Size : 500 kHz
- 1/2, 3'rd Harmonic : < -3 dBc
- Spurious Level : < -50 dBc
- Lock Time : < 20 ms
- Current Consumption : < 60 mA

Description

The plerow™ PLL synthesizer module was designed for use in wireless and wireline systems in a wide range of frequency from 50 MHz to 6 GHz. ASB's PLL provides exceptionally low spurious and phase noise performance with fast locking time and low current consumption. All products are available in a surface-mount type package.



Specifications

Parameter	Unit	Min.	Typical	Max.
Frequency Range	MHz	5700		5900
Output Power	dBm	-3	0	3
Supply Voltage	V	4.75	5	5.25
Current Consumption	mA		50	60
Channel Step Size	kHz		500	
1/2, 3'rd Harmonics	dBc		-15, -10	-8, -3
Spurious Level	dBc		-55	-50
Lock Time	ms		12	20
Reference Frequency	MHz		10	
Reference Input Level	dBm		0	
Phase Noise (C / N)				
@ 1 kHz			-73	-65
@ 10 kHz			-75	-68
@ 100 kHz			-95	-88
Output Impedance	Ω		50	
Operating Temp. Range	°C	-40	25	80
Package Type & Size	mm	SMT, 19.0W×19.0L×5.8H		

1) Measurement conditions are as follows: T = 25°C, V_{CC} = 5 V, Freq. = 5800 MHz, 50 ohm system.


More Information

Website: www.asb.co.kr
E-mail: sales@asb.co.kr

Tel: (82) 42-528-7223
Fax: (82) 42-528-7222

ASB Inc., 4th Fl. Venture Town
Bldg., 367-17 Goijeong-Dong,
Seo-Gu, Daejeon 302-716, Korea

Outline Drawing



Dimension (unit:mm) ±0.02														
A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
19.0 ±0.1	5.5	5.8	2.03	0.51	1.35	0.45	17.0	16.3	15.75	2.0	20.6	1.52	2.03	8.0

Pin No.	Application	Pin No.	Application
1	OSC IN	6	LD
3	CLOCK	9	VCC (VCO)
4	DATA	13	RF OUT
5	ENABLE	16	VCP (PLL)
All other Pins are Grounded			