


Recommended  
Panel Cut-Out



**Material:**

- Waterproof Rate: IP67
- LED Holder: PC+ABS, black
- LED:  $\varnothing$ 3MM, Green
- O-ring: EPDM, black
- Screw Nut: Nylon+GF
- Operating Temperature:  $-40^{\circ}\text{C} \sim +80^{\circ}\text{C}$
- For Panel Thickness 6.5MM Max.
- Forward Voltage: Green Typ. 2.2V/Max.2.4V
- Forward Current: Green Max. 30mA
- Reverse Voltage: 5V DC
- Luminous Intensity: Min.2,950/Typ.5,000(Mcd)

(QC) Quality Control: Important Dimension to check

Unit: MM $\pm$ 0.25MM

⊕ = Assmann logo



ITEM NO.

**A-LED8-1GAAS-PR7-1-R**

TITLE

Waterproof LED - Green color, M8 size connector,  
 $\varnothing$ 3MM, Plastic housing, Solder pins, IP67 unmated

**ASSMANN**  
Electronics, Inc.

1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283  
Toll Free: 1-877-277-6266 • Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED  
©Copyright 2010 by Assmann Electronic Components  
All International Rights Reserved