



■ Features :

- Built-in USB interface
- Cooling by free air convection(without fan)
- Slim size can fit in with the cup holder on vehicles
- High efficiency up to 90%
- 12V or 24V DC input
- Input voltage range: -15% ~ +25%
- Output voltage regulation:±10%
- Protections: Input reverse polarity/Bat. Low shutdown/Over voltage/Over load/Over temperature/Output short
- Output waveform: Modified sine wave
- Topology: Microprocessor
- Approvals: e13/ CE
- 1 year warranty



SPECIFICATION

ORDER NO.	A301-100-F3	A302-100-F3
OUTPUT	SAFETY MODEL NO.	A-100-150W(N)
	AC RATED VOLTAGE <small>Note.1</small>	230V
	RATED POWER	100W
	SURGE POWER	200W
	WAVEFORM	Modified Sine Wave
	FREQUENCY	50Hz±1%
	AC REGULATION	±10%
	STANDARD RECEPTACLES	Europe*1ea
	LED INDICATOR	Dual-color indicator display for power on / failure status
INPUT	USB POWER	5VDC / 500mA (max.)
	DC CURRENT	15A
	NO LOAD CURRENT DRAW	0.25A
	DC VOLTAGE	12V
	VOLTAGE RANGE	10 ~ 15VDC
	EFFICIENCY (Typ.)	90%
	DC CONNECTOR	650±50mm Cigarette plug*1ea
PROTECTION	FUSE	15A* 1ea
	BAT. LOW SHUTDOWN	10±0.5V
	OVER VOLTAGE	15 ~ 17V
	OVER TEMPERATURE	60±5°C / 140±9°F (case)
	OUTPUT SHORT	Shut-off
ENVIRONMENT	REVERSE. POLARITY	By fuse open
	WORKING TEMP.	0 ~ +30°C @100% load, 40°C @ 50% load
	WORKING HUMIDITY	20% ~ 90% RH non-condensing
	STORAGE TEMP., HUMIDITY	-30 ~ +70°C / -22 ~ +158°F, 10 ~ 95% RH
SAFETY & EMC	TEMP. COEFFICIENT	±0.05% / °C (0 ~ 50°C)
	ISOLATION RESISTANCE	I/P-O/P:100M Ohms min./ 500VDC / 25°C / 70% RH
	EMI CONDUCTION & RADIATION	Compliance to EN55022 class B, 72/ 245/ CEE, 2006/96/CE
	EMS IMMUNITY	Compliance to EN61000-4-2,3
OTHERS	LVD	Compliance to EN60950-1
	DIMENSION	φ 65*170mm (Diameter*L)
	PACKING	0.55Kg ; 30pcs / 17.5Kg / CARTON
	COOLING	By air convection
NOTE	1. AC rated output voltage is measured at 12.5VDC, 25VDC input voltage.	



100W Modified Sine Wave DC-AC Power Inverter

A301/302-100 series

■ Mechanical Specification

Unit:mm

