



## FULLY INSULATED PIGGYBACK QD'S

- Fully insulated with a rigid nylon housing
- Expanded flare version makes inserting dual wires easier
- Avikrimp version has a metal grip sleeve for extra insulation support



### Insulkrimp Standard Flare

Wire Range	Tab Size	Loose Piece Order No.	Mylar Tape Order No.	Max. Wire Insul. Dia.	Max. Width	Max. Length
22-18 AWG (0.3-1.0)	.250 x .032	19013-0001	19013-0002	0.140 (3.56)	0.38 (9.65)	0.86 (21.84)
16-14 AWG (1.2-2.0)	.250 x .032	19013-0005	19013-0006	0.165 (4.19)	0.38 (9.65)	0.86 (21.84)
12-10 AWG (3.0-6.0)	.250 x .032	19013-0018	19013-0016	0.280 (7.11)	0.38 (9.65)	1.02 (25.91)

### Insulkrimp Expanded Flare


Wire Range	Tab Size	Loose Piece Order No.	Mylar Tape Order No.	Max. Wire Insul. Dia.	Max. Width	Max. Length
22-18 AWG (0.3-1.0)	.250 x .032	19013-0003	19013-0004	0.230 (5.84)	0.38 (9.65)	0.94 (23.88)
16-14 AWG (1.2-2.0)	.250 x .032	19013-0007	19013-0008	0.260 (6.60)	0.38 (9.65)	0.94 (23.88)
12-10 AWG (3.0-6.0)	.250 x .032	19013-0018	19013-0016	0.280 (7.11)	0.38 (9.65)	1.02 (25.91)

### Avikrimp

Wire Range	Tab Size	Loose Piece Order No.	Mylar Tape Order No.	Max. Wire Insul. Dia.	Max. Width	Max. Length
18-22 AWG (0.8-0.35)	.250 x .032	19602-1100	19602-1101	0.120 (3.05)	0.39 (9.91)	0.88 (22.35)
14-16 AWG (2.00-1.30)	.250 x .032	19602-1200	19602-1201	0.141 (3.58)	0.39 (9.91)	0.88 (22.35)
10-12 AWG (5.00-3.30)	.250 x .032	19602-1300	19602-1301	0.233 (5.92)	0.38 (9.78)	1.02 (25.91)

## OPEN BARREL STRIP PIGGYBACK QD'S


- Open barrel strip version allows for rapid terminations



Wire Range	Tab Size	Max. Wire Insul. Dia.	Brass Order No.	Tin Plated Order No.	Max. Length
22-16 AWG (0.3-1.2)	.250 x .032	.145 (3.68)	19014-0001	19014-0002	.802 (20.4)
18-12 AWG (1.0-3.0)	.250 x .032	.180 (4.57)	19014-0003	19014-0004	.802 (20.4)

## OPEN BARREL STRIP LOCKING QD'S

- Locking lance sets the QD into place within the housing
- Fits into industry standard housings



Wire Range	Tab Size	Max. Wire Insul. Dia.	Brass Order No.	Tin Plated Order No.	Max. Length
22-16 AWG (0.3-1.2)	.250 x .032	.145 (3.68)	19015-0001	19015-0002	.802 (20.4)
18-12 AWG (1.0-3.0)	.250 x .032	.180 (4.57)	19015-0003	19015-0004	.802 (20.4)