

## General Description

The AO4607 uses advanced trench technology MOSFETs to provide excellent  $R_{DS(ON)}$  and low gate charge. The complementary MOSFETs may be used in inverter and other applications. A Schottky diode is co-packaged with the n-channel FET to minimize body diode losses. *AO4607 is Pb-free (meets ROHS & Sony 259 specifications). AO4607L is a Green Product ordering option. AO4607 and AO4607L are electrically identical.*


## Features

n-channel	p-channel
$V_{DS}$ (V) = 30V	-30V
$I_D$ = 6.9A ( $V_{GS}$ =10V)	-6A ( $V_{GS}$ =1.0V)
$R_{DS(ON)}$	$R_{DS(ON)}$
< 28mΩ ( $V_{GS}$ =10V)	< 35mΩ ( $V_{GS}$ = -10V)
< 42mΩ ( $V_{GS}$ =4.5V)	< 58mΩ ( $V_{GS}$ = - 4.5V)




## SCHOTTKY

$V_{DS}$  (V) = 30V, IF = 3A, VF<0.5V@1A



SOIC-8



### Absolute Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise noted

Parameter	Symbol	Max n-channel	Max p-channel	Units
Drain-Source Voltage	$V_{DS}$	30	-30	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	$\pm 20$	V
Continuous Drain Current <sup>A</sup>	$I_D$	6.9	-6	A
$T_A=70^\circ\text{C}$		5.8	-5	
Pulsed Drain Current <sup>B</sup>	$I_{DM}$	30	-30	
$T_A=25^\circ\text{C}$	$P_D$	2	2	W
$T_A=70^\circ\text{C}$		1.28	1.28	
Junction and Storage Temperature Range	$T_J$ , $T_{STG}$	-55 to 150	-55 to 150	°C
Parameter	Symbol	Maximum Schottky		Units
Reverse Voltage	$V_{DS}$	30		V
Continuous Forward Current <sup>A</sup>	$I_D$	3		A
$T_A=70^\circ\text{C}$		2		
Pulsed Diode Forward Current <sup>B</sup>	$I_{DM}$	20		
$T_A=25^\circ\text{C}$	$P_D$	2		W
$T_A=70^\circ\text{C}$		1.28		
Junction and Storage Temperature Range	$T_J$ , $T_{STG}$	-55 to 150		°C

<b>Thermal Characteristics: n-channel, Schottky and p-channel</b>						
<b>Parameter</b>		<b>Symbol</b>	<b>Device</b>	<b>Typ</b>	<b>Max</b>	<b>Units</b>
Maximum Junction-to-Ambient <sup>A</sup>	$t \leq 10s$	$R_{\theta JA}$	n-ch	48	62.5	°C/W
Maximum Junction-to-Ambient <sup>A</sup>	Steady-State		n-ch	74	110	°C/W
Maximum Junction-to-Lead <sup>C</sup>	Steady-State	$R_{\theta JL}$	n-ch	35	60	°C/W
Maximum Junction-to-Ambient <sup>A</sup>	$t \leq 10s$	$R_{\theta JA}$	p-ch	48	62.5	°C/W
Maximum Junction-to-Ambient <sup>A</sup>	Steady-State		p-ch	74	110	°C/W
Maximum Junction-to-Lead <sup>C</sup>	Steady-State	$R_{\theta JL}$	p-ch	35	40	°C/W
Maximum Junction-to-Ambient <sup>A</sup>	$t \leq 10s$	$R_{\theta JA}$	Schottky	47.5	62.5	°C/W
Maximum Junction-to-Ambient <sup>A</sup>	Steady-State		Schottky	71	110	°C/W
Maximum Junction-to-Lead <sup>C</sup>	Steady-State	$R_{\theta JL}$	Schottky	32	40	°C/W

**N-Channel + Schottky Electrical Characteristics ( $T_J=25^\circ\text{C}$  unless otherwise noted)**

Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>STATIC PARAMETERS</b>						
$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$I_D=250\mu\text{A}, V_{GS}=0\text{V}$	30			V
$I_{\text{DSS}}$	Zero Gate Voltage Drain Current. (Set by Schottky leakage)	$V_R=30\text{V}$		0.007	0.05	mA
		$V_R=30\text{V}, T_J=125^\circ\text{C}$		3.2	10	
		$V_R=30\text{V}, T_J=150^\circ\text{C}$		12	20	
$I_{\text{GSS}}$	Gate-Body leakage current	$V_{DS}=0\text{V}, V_{GS}=\pm 20\text{V}$			100	nA
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	1	1.9	3	V
$I_{\text{D(ON)}}$	On state drain current	$V_{GS}=4.5\text{V}, V_{DS}=5\text{V}$	20			A
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{GS}=10\text{V}, I_D=6.9\text{A}$		22.5	28	$\text{m}\Omega$
		$T_J=125^\circ\text{C}$		31.3	38	
$g_{\text{FS}}$	Forward Transconductance	$V_{DS}=5\text{V}, I_D=6.9\text{A}$	10	15.4		S
$V_{\text{SD}}$	Body-Diode+Schottky Forward Voltage	$I_S=1\text{A}$		0.45	0.5	V
$I_S$	Maximum Body-Diode+Schottky Continuous Current				5.5	A
<b>DYNAMIC PARAMETERS</b>						
$C_{\text{iss}}$	Input Capacitance	$V_{GS}=0\text{V}, V_{DS}=15\text{V}, f=1\text{MHz}$		680	820	pF
$C_{\text{oss}}$	Output Capacitance (FET+Schottky)			131		pF
$C_{\text{rss}}$	Reverse Transfer Capacitance			77		pF
$R_g$	Gate resistance	$V_{GS}=0\text{V}, V_{DS}=0\text{V}, f=1\text{MHz}$		3	3.6	$\Omega$
<b>SWITCHING PARAMETERS</b>						
$Q_g(10\text{V})$	Total Gate Charge	$V_{GS}=10\text{V}, V_{DS}=15\text{V}, I_D=6.9\text{A}$		13.84	16.6	nC
$Q_g(4.5\text{V})$	Total Gate Charge			6.74		nC
$Q_{\text{gs}}$	Gate Source Charge			1.82		nC
$Q_{\text{gd}}$	Gate Drain Charge			3.2		nC
$t_{\text{D(on)}}$	Turn-On Delay Time	$V_{GS}=10\text{V}, V_{DS}=15\text{V}, R_L=2.2\Omega, R_{\text{GEN}}=3\Omega$		4.6		ns
$t_r$	Turn-On Rise Time			4.1		ns
$t_{\text{D(off)}}$	Turn-Off Delay Time			20.6		ns
$t_f$	Turn-Off Fall Time			5.2		ns
$t_{\text{rr}}$	Body-Diode+Schottky Reverse Recovery Time	$I_F=6.9\text{A}, dI/dt=100\text{A}/\mu\text{s}$		13.7	16.5	ns
$Q_{\text{rr}}$	Body-Diode+Schottky Reverse Recovery Charge	$I_F=6.9\text{A}, dI/dt=100\text{A}/\mu\text{s}$		4.1		nC

A: The value of  $R_{\text{JJA}}$  is measured with the device mounted on 1in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ . The value in any given application depends on the user's specific board design. The current rating is based on the  $t \leq 10\text{s}$  thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C. The  $R_{\text{JJA}}$  is the sum of the thermal impedance from junction to lead  $R_{\text{JUL}}$  and lead to ambient.

D. The static characteristics in Figures 1 to 6 are obtained using 80  $\mu\text{s}$  pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ . The SOA curve provides a single pulse rating.

F. The Schottky appears in parallel with the MOSFET body diode, even though it is a separate chip. Therefore, we provide the net forward drop, capacitance and recovery characteristics of the MOSFET and Schottky. However, the thermal resistance is specified for each chip separately

Rev 4: Sept 2005

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

## TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: N-CHANNEL




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature





Figure 5: On-Resistance vs. Gate-Source Voltage

Figure 6: Body diode with parallel Schottky characteristics  
(Note F)

## TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: N-CHANNEL




Figure 7: Gate-Charge characteristics




Figure 8: Capacitance Characteristics: MOSFET + Parallel Schottky




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance

**P-Channel Electrical Characteristics ( $T_J=25^\circ\text{C}$  unless otherwise noted)**

Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>STATIC PARAMETERS</b>						
$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$I_D=-250\mu\text{A}, V_{GS}=0\text{V}$	-30			V
$I_{\text{DSS}}$	Zero Gate Voltage Drain Current	$V_{DS}=-24\text{V}, V_{GS}=0\text{V}$ $T_J=55^\circ\text{C}$			-1 -5	$\mu\text{A}$
$I_{\text{GSS}}$	Gate-Body leakage current	$V_{DS}=0\text{V}, V_{GS}=\pm20\text{V}$			$\pm100$	nA
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=-250\mu\text{A}$	-1.2	-2	-2.4	V
$I_{\text{D(ON)}}$	On state drain current	$V_{GS}=-10\text{V}, V_{DS}=-5\text{V}$	30			A
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{GS}=-10\text{V}, I_D=-6\text{A}$ $T_J=125^\circ\text{C}$		28 37	35 45	$\text{m}\Omega$
		$V_{GS}=-4.5\text{V}, I_D=-5\text{A}$		44	58	$\text{m}\Omega$
$g_{\text{FS}}$	Forward Transconductance	$V_{DS}=-5\text{V}, I_D=-6\text{A}$		13		S
$V_{\text{SD}}$	Diode Forward Voltage	$I_S=-1\text{A}, V_{GS}=0\text{V}$		-0.76	-1	V
$I_S$	Maximum Body-Diode Continuous Current				-4.2	A
<b>DYNAMIC PARAMETERS</b>						
$C_{\text{iss}}$	Input Capacitance	$V_{GS}=0\text{V}, V_{DS}=-15\text{V}, f=1\text{MHz}$		920	1100	pF
$C_{\text{oss}}$	Output Capacitance			190		pF
$C_{\text{rss}}$	Reverse Transfer Capacitance			122		pF
$R_g$	Gate resistance	$V_{GS}=0\text{V}, V_{DS}=0\text{V}, f=1\text{MHz}$		3.6	4.4	$\Omega$
<b>SWITCHING PARAMETERS</b>						
$Q_g(10\text{V})$	Total Gate Charge (10V)	$V_{GS}=-10\text{V}, V_{DS}=-15\text{V}, I_D=-6\text{A}$		18.5	22.2	nC
$Q_g(4.5\text{V})$	Total Gate Charge (4.5V)			9.6		nC
$Q_{\text{gs}}$	Gate Source Charge			2.7		nC
$Q_{\text{gd}}$	Gate Drain Charge			4.5		nC
$t_{\text{D(on)}}$	Turn-On DelayTime	$V_{GS}=-10\text{V}, V_{DS}=-15\text{V}, R_L=2.7\Omega, R_{\text{GEN}}=3\Omega$		7.7		ns
$t_r$	Turn-On Rise Time			5.7		ns
$t_{\text{D(off)}}$	Turn-Off DelayTime			20.2		ns
$t_f$	Turn-Off Fall Time			9.5		ns
$t_{\text{rr}}$	Body Diode Reverse Recovery Time	$I_F=-6\text{A}, dI/dt=100\text{A}/\mu\text{s}$		20	24	ns
$Q_{\text{rr}}$	Body Diode Reverse Recovery Charge	$I_F=-6\text{A}, dI/dt=100\text{A}/\mu\text{s}$		8.8		nC

A: The value of  $R_{\theta JA}$  is measured with the device mounted on 1 in <sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ . The value in any given application depends on the user's specific board design. The current rating is based on the  $t \leq 10\text{s}$  thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C. The  $R_{\theta JA}$  is the sum of the thermal impedance from junction to lead  $R_{\theta JL}$  and lead to ambient.

D. The static characteristics in Figures 1 to 6,12,14 are obtained using 80  $\mu\text{s}$  pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in <sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ . The SOA curve provides a single pulse rating.

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

Rev 4: Sept 2005

## TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: P-CHANNEL




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

## TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: P-CHANNEL




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance