


PRELIMINARY
 Notice: This is not a final specification.
 Some parametric limits are subject to change.

MITSUBISHI Pch POWER MOSFET


FX50KMJ-2

HIGH-SPEED SWITCHING USE

FX50KMJ-2



- 4V DRIVE
- V_{DSS} -100V
- $r_{DS(ON)}$ (MAX) $50m\Omega$
- I_D -50A
- Integrated Fast Recovery Diode (TYP.) 100ns
- V_{iso} 2000V



APPLICATION

Motor control, Lamp control, Solenoid control
 DC-DC converter, etc.

MAXIMUM RATINGS (Tc = 25°C)





Symbol	Parameter	Conditions	Ratings	Unit
V_{DSS}	Drain-source voltage	$V_{GS} = 0V$	-100	V
V_{GSS}	Gate-source voltage	$V_{DS} = 0V$	± 20	V
I_D	Drain current		-50	A
I_{DM}	Drain current (Pulsed)		-200	A
I_{DA}	Avalanche drain current (Pulsed)	$L = 30\mu H$	-50	A
I_S	Source current		-50	A
I_{SM}	Source current (Pulsed)		-200	A
P_D	Maximum power dissipation		35	W
T_{ch}	Channel temperature		-55 ~ +150	°C
T_{stg}	Storage temperature		-55 ~ +150	°C
V_{iso}	Isolation voltage	AC for 1minute, Terminal to case	2000	V
—	Weight	Typical value	2.0	g

PRELIMINARY
 Notice: This is not a final specification.
 Some parametric limits are subject to change.

ELECTRICAL CHARACTERISTICS (Tch = 25°C)


Symbol	Parameter	Test conditions	Limits			Unit
			Min.	Typ.	Max.	
V (BR) DSS	Drain-source breakdown voltage	Id = -1mA, Vgs = 0V	-100	—	—	V
IGSS	Gate-source leakage current	Vgs = ±20V, Vds = 0V	—	—	±0.1	μA
IdSS	Drain-source leakage current	Vds = -100V, Vgs = 0V	—	—	-0.1	mA
VGS (th)	Gate-source threshold voltage	Id = -1mA, Vds = -10V	-1.0	-1.5	-2.0	V
rDS (ON)	Drain-source on-state resistance	Id = -25A, Vgs = -10V	—	39	50	mΩ
rDS (ON)	Drain-source on-state resistance	Id = -25A, Vgs = -4V	—	47	61	mΩ
VDS (ON)	Drain-source on-state voltage	Id = -25A, Vgs = -10V	—	-0.98	-1.25	V
yfs	Forward transfer admittance	Id = -25A, Vds = -10V	—	49.2	—	S
Ciss	Input capacitance	Vds = -10V, Vgs = 0V, f = 1MHz	—	11130	—	pF
Coss	Output capacitance		—	896	—	pF
Crss	Reverse transfer capacitance		—	480	—	pF
td (on)	Turn-on delay time		—	57	—	ns
tr	Rise time	VDD = -50V, Id = -25A, Vgs = -10V, RGEN = RGS = 50Ω	—	118	—	ns
td (off)	Turn-off delay time		—	828	—	ns
tf	Fall time		—	380	—	ns
VSD	Source-drain voltage		Is = -25A, Vgs = 0V	—	-1.0	-1.5
Rth (ch-c)	Thermal resistance	Channel to case	—	—	3.57	°C/W
trr	Reverse recovery time	Is = -50A, dis/dt = 100A/μs	—	100	—	ns

PERFORMANCE CURVES




PRELIMINARY
 Notice: This is not a final specification.
 Some parametric limits are subject to change.


ON-STATE VOLTAGE VS. GATE-SOURCE VOLTAGE (TYPICAL)




ON-STATE RESISTANCE VS. DRAIN CURRENT (TYPICAL)




TRANSFER CHARACTERISTICS (TYPICAL)




FORWARD TRANSFER ADMITTANCE VS. DRAIN CURRENT (TYPICAL)



CAPACITANCE VS. DRAIN-SOURCE VOLTAGE (TYPICAL)




SWITCHING CHARACTERISTICS (TYPICAL)




PRELIMINARY
 Notice: This is not a final specification.
 Some parametric limits are subject to change.


GATE-SOURCE VOLTAGE VS. GATE CHARGE (TYPICAL)




SOURCE-DRAIN DIODE FORWARD CHARACTERISTICS (TYPICAL)




ON-STATE RESISTANCE VS. CHANNEL TEMPERATURE (TYPICAL)



THRESHOLD VOLTAGE VS. CHANNEL TEMPERATURE (TYPICAL)



BREAKDOWN VOLTAGE VS. CHANNEL TEMPERATURE (TYPICAL)



TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS

