

Part Number: C1202

Revision Level: 1

Date: 11/6/2007

2C 18 AWG 41/34 TC RUBBER OAS CAROLPRENE*

Audio/Video & Broadcast Cable

A. CONSTRUCTION

Conductor: #18 AWG 41/34 Tinned Copper
 Insulation: 0.020" Wall Rubber
 Cable: 2C @ 1.75" LHL with jute filler & overall mylar wrap.
 Braid: #36 AWG Tinned Copper, 80% Min. Coverage
 Jacket: 0.035" Wall Carolprene* - Black
 Print Legend: **CAROL -- C1202A -- VW-1 MADE IN USA**

DIAMETERS

0.049" nom.
 0.091" nom.
 0.182" nom.
 0.182" nom.
 0.295" +/- 0.015"

B. INDUSTRY APPROVALS

None

C. ELECTRICAL PROPERTIES

TEMPERATURE: 60C
 SUGGESTED WORKING VOLTAGE (V_{rms}): 300V
 CONDUCTOR D.C. RESISTANCE: 7.1 Ohms/1000 ft nom
 SHIELD RESISTANCE: 3.2 Ohms/1000 ft nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	White
2	Black