

AX61133TM

1U Rackmount Chassis for ATX Motherboard

NEW



Supports 2 x 3.5" hot-swappable SATA HDD tray
Easy-to-maintain tray design

Features

- Supports 12" x 9.6" standard ATX MB
- Supports two 3.5" SATA HDD (hot-swappable tray)
- SupportS one PCI or PCIe riser card
- Supports ATX 270W power supply



▲ Front view



▲ Rear view



DDR3

Specifications

Standard Color	Black
Construction	Heavy-duty steel
Drive Capacity	Exposed 2 x SATA HDD drive bay (hot swappable tray)
Cooling	2 x 4 cm ball bearing fans (15.3 CFM/each)
Front Panel Indicators	1 x power on/off, 1 x HDD
Front Panel Controls	1 x power on/off
Front Panel Connectors	N/A
Pre-punched Panel	N/A
System Board	12" x 9.6" standard ATX MB

Expansion Interface	1 x PCI slot (32 bits/33MHz) or 1 x PCIe slot
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)Range
Dimensions	473.5 mm (19") (W) x 440 mm (17.32") (D) x 44 mm (1.73") (H)
Weight (net/gross)	9.8 kg (21.6 lb)/10.8 kg (23.8 lb)

Power Supply Specifications

Items	Watt	Input	Specifications	MTBF
			Output	
PS270-1U	ATX 270W (PFC)	AC 90-264V (Auto)	+5V @ 18A	100,000 hours
			+12V 1 @ 16A	
			+12V 2 @ 10A	
			+3.3V @ 16A	
			-12V @ 0.8A	
			+5VSB @ 2.5A	

Ordering Information

AX61133TM/X270 With ATX 270W power supply

*Specifications and certifications are based on options and may vary.

Recommended MB Selections

IMB206 with LGA1156 heatsink (manufacture option)
 IMB207 with LGA1156 heatsink (manufacture option)
 IMB208 with LGA1156 heatsink (manufacture option)

Optional Items

E296200100	AX96200 1-slot PCI 32 bit riser card
84A61611010E	PCIe x 16 riser card L:50mm

Overview

Embedded
Systems

Embedded
Systems for
Transportation

Embedded
Field
Controllers

Embedded
MicroBoxes

Industrial
Barebone
Systems

Industrial
Chassis

Backplanes

Power
Supplies

Peripherals &
Accessories

Appendix

Dimensions

