



Micro Commercial Components



Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

LL60
LL60P

Features

- High Reliability
- Low Reverse Current and Low Forward Voltage
- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

Maximum Ratings

- Operating Temperature: -65°C to +125°C
- Storage Temperature: -65°C to +125°C


Electrical Characteristics @ 25°C Unless Otherwise Specified

Parameter	Symbol	Type	Value	Test Condition
Repetitive Peak Reverse Voltage	V _{RRM}	LL60	40V	
		LL60P	45V	
Average Forward Current	I _{F(AV)}	LL60	30mA	T _a = 25°C
		LL60P	50mA	T _a = 25°C
Peak Forward Surge Current	I _{FSM}	LL60	150mA	t _p ≤ 1s
		LL60P	500mA	t _p ≤ 1s
Junction Ambient	R _{thJA}		250K/W	On PC board 50mm × 50mm × 1.6mm

Note:1.Lead in Glass Exemption Applied, see EU Directive Annex 5.


Schottky Barrier Rectifier

MiniMELF



DIM	DIMENSIONS				NOTE
	INCHES		MM		
A	.130	.146	3.30	3.70	
B	.008	.016	.20	.40	
C	.055	.059	1.40	1.50	∅

SUGGESTED SOLDER PAD LAYOUT



Electrical Characteristics @ 25°C Unless Otherwise Specified

Parameter	Test Conditions	Type	Symbol	Min	Typ	Max	Unit
Forward voltage	I _F =1mA	LL60	V _F	---	0.32	0.5	V
		LL60P	V _F	---	0.24	0.5	V
	I _F =30mA	LL60	V _F	---	0.65	1.0	V
		LL60P	V _F	---	0.65	1.0	V
Reverse current	V _R =15V	LL60	I _R	---	0.1	0.5	μA
		LL60P	I _R	---	0.5	1.0	μA
Junction capacitance	V _R =1V, f=1MHz	LL60	C _J	---	2.0	---	pF
	V _R =10V, f=1MHz	LL60P	C _J	---	6.0	---	pF
Reverse recovery time	I _F =I _R =1mA, I _{rr} =1mA R _C =100Ω		t _{rr}	---	---	1.0	ns



TM

Micro Commercial Components

Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel: 2.5Kpcs/Reel

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com