

# NA-340

Desktop Network Appliance Platform with Intel® Atom™ Processor D525 and 6 LANs



▲ Front view



▲ Rear view



Low Power

## Introduction

NA-340 is a compact network hardware platform for VPN, Firewall, UTM and other network applications. It supports low power Intel® Atom™ processor D425/ D525 1.8 GHz with Intel® ICH8M PCH chipset and features a 1U desktop form factor. The system supports up to 4 GB of DDR3 800 memory. In addition, NA-340 features one internal 2.5" HDD for storing event log. To prevent problems from sudden shutdown, the NA-340 supports LAN bypass function through software program (optional). Meantime, the Mini PCIe card is for WiFi wireless card installation.

## Specifications

System	
CPU	Intel® Atom™ processor D525 1.8 GHz with 1M L2 cache
Chipset	Intel® ICH8M PCH chipset
Memory	1 x DDR3 800 (single channel) SO-DIMM max. up to 4 GB (unbuffered non-ECC)
BIOS	AMI PnP Flash BIOS with function of BIOS redirected to COM port
HDD Interface	1 x 2.5 SATA HDD
Network Interface	6 x 10/100/1000Mbps Ethernet (Intel® 82583V (default), Intel® 82574L (optional))
SSD	1 x CFast™ 1 x CompactFlash™ type-II (optional)
I/O Interface	1 x RS-232 (RJ-type connector), 2 x USB connector, 6 x RJ-45 connector, 1 x DC-in power jack (power din as option)
Watchdog Timer	Up to 8 stepping for porting
USB	2 x USB 2.0 port on rear side, rest are internal pin headers
Expansion Slot	PCIe Mini Card (USB transaction bus)
Other Features (optional)	LAN bypass function through latch relay (one group)
Power Supply	1 x 12V, 5A power adapter
OS Compatibility	Linux Redhat Kernel 2.6

## Mechanical/ Environmental

Form Factor	1U desktop
LED	Power, HDD, Link/Act with transfer rate, LAN bypass (optional), GPIO programmable (optional)
Operating Temp.	0° ~ +40°C (32°F ~ 104°F)
Storage Temp.	-20° ~ +70°C (-4°F ~ +158°F)
Humidity	10% ~ 90% RH, non-condensing
Chassis Material	Steel
Dimensions	44 mm (1.73") (H) x 230 mm (9.00") (W) x 152.1 mm (5.98") (D)
Weight (net/gross)	2.5 kg (5.5 lb)/2.9 kg (6.39 lb)
Certification	FCC class B/CE class B

## Features

- Low power and high performance Intel® Atom™ processor D525 1.8 GHz with 1M/512K L2 cache and Intel® ICH8M PCH chipset
- Supports 6 10/100/1000Mbps Ethernet ports (Intel® 82583V is default)
- Supports BIOS redirected to COM port
- Supports one 2.5" SATA HDD
- Suitable for VPN, network bandwidth controller, firewall applications
- Supports Intel® Hyper-threading technology
- Supports BIOS Quick Boot
- Supports Smart Fan for better thermal and acoustic performance

## Ordering Information

### Standard

NA-340-D6GI-D525-RC w/ Lan bypass	Compact network appliance with Intel® Atom™ processor D525 1.8 GHz, 6 10/100/1000Mbps (Intel® 82583V) and LAN bypass
NA-340-D6GI-D525-RC w/o LAN bypass	Compact network appliance with Intel® Atom™ processor D525 1.8 GHz, 6 10/100/1000Mbps (Intel® 82583V) and w/o LAN bypass

### Optional

CK9A104	Cable kit (P/N: 8816E320010E)
59416112100E	Cable DB9 (M) - RJ-45, L: 1.5M straight cable

\* Specifications and certifications are based on options and may vary.

\*\* Recommend ordering optional cable kit with first order.

## Packing List

1 x DC power adapter 12V/5A
1 x SATA cable
1 x utility CD (user's manual and driver)
1 x RJ-45 to DB9 (F) 1.8M

## Dimensions

