



# RFID Transponder Coils – 5315TC



The 5315TC is Coilcraft's most rugged and lowest cost antenna coil designed for RFID applications at 125 kHz. The wrap-around terminals have large mounting surfaces to ensure excellent board adhesion. The coil is wound on a plastic base, providing great durability and allowing this part to withstand harsh mechanical shock.

In addition to the standard models shown, Coilcraft can design transponder coils to operate at other frequencies.

Coilcraft **Designer's Kit C169** contains four samples each of the standard parts shown. To order, contact Coilcraft or visit <http://order.coilcraft.com>.

Part number <sup>1</sup>	Inductance <sup>2</sup> at 125 kHz ±2% (mH)	Q <sub>min</sub> <sup>2</sup>	Read distance <sup>3</sup> (inches/cm)	Sensitivity <sup>4</sup> (mV/μT)	Matching capacitor <sup>5</sup> (pF)	DCR max <sup>6</sup> (Ohms)	SRF <sub>typ</sub> <sup>7</sup> (kHz)
5315TC-374XGB_	0.37	8	16 / 40.6	8.32	4380	24	7100
5315TC-404XGB_	0.40	8	17 / 43.2	8.67	4050	25	7300
5315TC-704XGB_	0.70	12	21 / 53.3	11.43	2320	33	4500
5315TC-904XGB_	0.90	12	21 / 53.3	13.35	1800	38	3800
5315TC-105XGB_	1.00	12	23 / 58.4	14.07	1600	40	2500
5315TC-115XGB_	1.08	13	23 / 58.4	14.65	1500	40	2300
5315TC-205XGB_	1.97	14	25 / 63.5	21.28	820	70	2300
5315TC-245XGB_	2.38	12	26 / 66.0	23.97	680	80	2400
5315TC-335XGB_	3.30	14	27 / 68.6	29.70	490	95	1800
5315TC-415XGB_	4.15	15	29 / 73.7	34.95	390	103	1260
5315TC-495XGB_	4.90	15	28 / 71.1	40.00	330	150	1550
5315TC-685XGB_	6.80	13	30 / 76.2	53.87	240	180	1350
5315TC-715XGB_	7.10	14	30 / 76.2	55.41	220	176	890
5315TC-725XGB_	7.20	17	30 / 76.2	56.74	220	165	880

1. When ordering, please specify **packaging** code:

**5315TC-715XGB D**

**Packaging:** D = 13" machine-ready reel. EIA-481 embossed plastic tape (3000 parts per full reel).

B = Less than full reel. In tape, but not machine ready. To have a leader and trailer added (\$25 charge), use code letter D instead.

2. Inductance and Q measured using Agilent/HP 4192A impedance analyzer at 125 kHz. For recommended test procedures, contact Coilcraft.

3. Read distance measured using the KEELOQ® Transponder Evaluation Kit part number DM303005 from Microchip. Distance was recorded as the voltage across the resonant circuit dropped below 10 mV.

4. Sensitivity measured in accordance with Coilcraft application note "Measuring Sensitivity of Transponder Coils."

5. Matching capacitor value required for parallel resonant circuit operating at 125 kHz.

6. DCR measured on micro-ohmmeter.

7. SRF measured using Agilent/HP 8753D network analyzer.

8. Operating temperature range -40°C to +125°C.

9. Electrical specifications at 25°C.

See Qualification Standards section for environmental and test data.

## Coilcraft®

Specifications subject to change without notice.

Please check our website for latest information. Document 311-1 Revised 12/04/03


1102 Silver Lake Road Cary, Illinois 60013 Phone 847/639-6400 Fax 847/639-1469

E-mail [info@coilcraft.com](mailto:info@coilcraft.com) Web <http://www.coilcraft.com>




# RFID Transponder Coils – 5315TC

## Typical L vs Frequency



## Dimensions



**Terminations:** Nickel/gold over phos bronze  
**Tape and reel:** 3000/13" reel 24 mm tape width  
 For packaging data see Tape and Reel Specifications section.



Specifications subject to change without notice.  
 Please check our website for latest information. Document 311-2 Revised 03/15/05

1102 Silver Lake Road Cary, Illinois 60013 Phone 847/639-6400 Fax 847/639-1469

E-mail [info@coilcraft.com](mailto:info@coilcraft.com) Web <http://www.coilcraft.com>