

Power Supplies - 1U Type

PS200-1U

| | | | | | | | |
|----------------------|--------------------------------------|--|-------|-------|-------|------|-------|
| Model Name | P/N: 50914506010E | | | | | | |
| PS200-1U ATX 200W | Input Range | 90 – 260Vac Full Range | | | | | |
| | Output Voltage | +5V | +3.3V | +12V1 | +12V2 | -12V | +5Vsb |
| | | 17A | 14A | 6A | 12A | 0.8A | 2A |
| | MTBF (hours) | AT 25°C 100,000h | | | | | |
| | Safety | CB, TUV, CE, FCC, C-TICK, CUL, UL, CCC | | | | | |
| | Dimensions | 150 x 81.5 x 40.5 mm | | | | | |
| | Compatible with Axiomtek Products | AX61120, AX60530 | | | | | |



PS270-1U

| | | | | | | | |
|-------------------|--------------------------------------|---|-------------------|-----------------|-----------------|------|------|
| Model Name | P/N: 50954A24110E | | | | | | |
| PS270-1U ATX 270W | Input Range | 90 – 264Vac Full Range | | | | | |
| | Output Voltage | +5V | +3.3V | +12V1 | +12V2 | -12V | -12V |
| | | 18A (0.5A min) | 16A (0.5A min) | 16A (1A min) | 10A (1A min) | 0.8A | 0.8A |
| | MTBF (hours) | AT 25°C 100,000h | | | | | |
| | Safety | TUV, CSA22.2 NO.60950-1, IEC, UL, NEMKO, CE | | | | | |
| | Dimensions | 150 x 81.5 x 40.5 mm | | | | | |
| | Compatible with Axiomtek Products | AX61120/AX60530 | | | | | |

