

Part Number: C1210

Revision Level: 3

Date: 11/20/2007

10C 18 AWG 41/34 TC RUBBER OAS CAROLPRENE*

CONTROL CABLE

A. CONSTRUCTION

DIAMETERS

Conductor:	#18 AWG 41/34 Tinned Copper	0.051" nom.
Insulation:	0.020" Wall Rubber	0.091" nom.
Cable:	10 conductors @ 1.0" LHL with jute filler & overall mylar wrap.	0.318" nom.
Braid	#36 AWG Tinned Copper 80% Min. Coverage	0.340" nom.
Tape:	Cotton Separator	0.350" nom.
Jacket:	0.035" Wall Carolprene* - Black	0.425" +/- 0.021"
Print Legend:	CAROL C-1210A VW-1 MADE IN USA	

B. INDUSTRY APPROVALS

NONE

C. ELECTRICAL PROPERTIES

TEMPERATURE:	60 C
SUGGESTED WORKING VOLTAGE (Vrms):	300Vrms
CONDUCTOR D.C. RESISTANCE:	7.1 Ohms/1000 ft nom

D. COLOR CODE *(Listed as Individual Conductors or Pairs of Conductors)*

1	Black
2	White
3	Red
4	Green
5	Blue
6	Brown
7	Yellow
8	Orange
9	Gray
10	Purple