



Metrological approval

- Test certificate: applied for.

European directives

- Directive 89/336/EC relative to *Electromagnetic Compatibility**
- Directive 73/23/EC relative to *Low Voltage Equipment*.

Printing characteristics

- Printing speed: 200 cps (at 10 cpi).
- Printing density: 216 dpi.
- Character size:

	height	width
Single	2.5 mm	2 mm
Double	2.5 mm	4 mm

General

The LQ 300 printer is a 24 needles dot matrix printer printing alphanumerical data in up to 160 characters wide lines (at 20 cpi) on:

- listing paper,
- tickets,
- adhesive labels.

Paper format

- Paper roll width: 254 mm
- Number of copies: max. 1 original + 3 copies

Application

The printer has been designed for use in commercial and industrial environments where high speed printing is required.

Paper feed

- Friction or tractor feed.

Master instruments

The LQ 300 printer may be connected to the following indicators and terminals:

- C range
- M range
- T 2500
- Process
- ICT self-service weighing terminal
- I 200 range
- PC

* Meeting the conditions of this Directive directly depends on a correct installation.

Physical characteristics

- Weight approx. 4.3 kg
- Height www.DataSheet4U.com 141 mm
- Width:
 - without paper feed knob 366 mm
 - with paper feed knob 390 mm
- Depth 275 mm

Electrical characteristics

- Power supply 220-240 V
- Frequency 50 Hz
- Power consumption:
 - in operation 30 W
 - in stand-by mode 10 W

Environmental conditions

- Temperature range:
 - operation +5°C / +35°C
 - operation: (with envelopes, labels or recycled paper) +15°C / +25°C
 - storage -20°C / +55°C
- Relative humidity:
 - operation 5 to 80 %
 - operation: (with envelopes, labels or recycled paper) 20 to 60 %
 - storage 5 to 85 %

Connection

- Serial RS 232 interface and parallel Centronics interface.
- Baudrate: 1200 - 2400 - 4800 - 9600 baud

PRECIA-MOLEN	
INSTRUMENTS DE PESAGE POUR L'INDUSTRIE ET LE COMMERCE 07000 PRIVAS CEDEX TEL. 04.75.66.46.00 FAX 04.75.65.83.30	
Le 15/12/1998	No. DE TICKET: 18 A 16h20
CLIENT :#11111111	

PRODUIT	: (kg)

22222222	:N: 00.354
33333333	:N: 00.606
44444444	:N: 01.531
55555555	:N: 02.279
66666666	:N: 01.976
77777777	:N: 01.544
88888888	:N: 02.671

NB. DE PESEES: 7	
TOTAL	10.961

RECAPITULATIF						
Date : 27/02/98						
!	DATE	!	NO PESEE	!	REF1	!
!	HEURE	!	NO CARTON	!	REF2	!
!	27/02/98	!	1	!	1275	!
!	08h38	!	1455x07	!	1105	!
!		!		!	2001	!
!		!		!	2601	!
!		!		!	4900	!
!		!		!	12000	!
!		!		!	7500	!

The data printed out and the presentation of the above examples directly depend on the possibilities offered by the indicator/terminal to which the printer has been connected.

Your weighing specialist

Illustrations are not contractual. Precia-Molen reserves the right to modify at any time, without prior notice, the information contained in this leaflet.

Offices and Factory
P.O. Box 106 - F 07000 Privas - France
Tel. 33 (0) 475 664 600
Fax 33 (0) 475 658 330
E-MAIL webmaster@preciamolen.com

RCS : 386 620 165 RCS Aubenas

