

Part Number: E1052S

Revision Level: 702

Date: 10/29/2007

2C 14 19/0.0147 BC SR-PVC PVC

Sound, Alarm & Security Cable

A. CONSTRUCTION

Conductor:	#14 AWG 19/0.0147 Bare Copper	0.071" nom.
Insulation:	0.013" Wall Semi-Rigid Polyvinyl Chloride	0.097" nom.
Cable:	2C @ 4.00" LHL	0.193" nom.
Jacket:	0.015" Wall Polyvinyl Chloride – Gray	0.224" +/- 0.011"
Print Legend:	<i>CAROL A (R) 14 AWG - - E1052S - - 75C E60233-8 (UL) CL3R --- MADE IN USA (DATE CODE & SEQUENTIAL FOOTAGE 1000' TO 0')</i>	

DIAMETERS

B. INDUSTRY APPROVALS

National Electrical Code	Article 725
UL Standard 13	Type CL3R

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75C
SUGGESTED WORKING VOLTAGE (V _{rms}):	300V
CONDUCTOR D.C. RESISTANCE:	2.6 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	32.47 pF/ft @ 1kHz nom
CHARACTERISTIC IMPEDANCE:	59.2 Ohms @ 1MHz nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	Red