

**1 310 nm FOR 2.5 Gb/s
 InGaAsP MQW-DFB LASER DIODE**

DESCRIPTION

The NX6307 Series is a 1 310 nm Multiple Quantum Well (MQW) structured Distributed Feed-Back (DFB) laser diode with InGaAs monitor PIN-PD. This device is ideal for Synchronous Digital Hierarchy (SDH) system, short haul and long haul STM-16, ITU-T recommendations.



FEATURES

- | | |
|------------------------------------|--|
| • Optical output power | $P_o = 7.0 \text{ mW}$ |
| • Low threshold current | $I_{th} = 10 \text{ mA @ } T_c = 25^\circ\text{C}$ |
| • High speed | $t_r, t_f = 0.2 \text{ ns MAX.}$ |
| • SMSR | 45 dB @ TYP. |
| • Wide operating temperature range | $T_c = -20 \text{ to } +85^\circ\text{C}$ |
| • InGaAs monitor PIN-PD | |
| • CAN package | $\phi 5.6 \text{ mm}$ |
| • Based on Telcordia reliability | |



The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version.
 Not all devices/types available in every country. Please check with local NEC Compound Semiconductor Devices representative for availability and additional information.

PACKAGE DIMENSIONS (UNIT: mm)



ORDERING INFORMATION

NX6307S Series

Part Number	Package	Pin Connections
NX6307SH	4-pin CAN with flat glass cap	
NX6307SI		
NX6307SJ		
NX6307SK		

NX6307G Series

Part Number	Package	Pin Connections
NX6307GH	4-pin CAN with aspherical lens cap	
NX6307GI		
NX6307GJ		
NX6307GK		

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Ratings	Unit
Optical Output Power	P _o	20	mW
Forward Current of LD	I _F	150	mA
Reverse Voltage of LD	V _R	2.0	V
Forward Current of PD	I _F	10	mA
Reverse Voltage of PD	V _R	20	V
Operating Case Temperature	T _C	-20 to +85	°C
Storage Temperature	T _{stg}	-40 to +85	°C
Assembly Temperature	T _{asb}	150 (15 Hr)	°C
Lead Soldering Temperature	T _{slid}	350 (3 sec.)	°C
Relative Humidity (noncondensing)	RH	85	%


ELECTRO-OPTICAL CHARACTERISTICS (T_C = 25°C, unless otherwise specified)

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Operating Voltage	V _{op}	P _o = 7.0 mW, T _C = -20 to +85°C		1.1	1.6	V
Threshold Current	I _{th}			10	20	mA
		T _C = 85°C		30	40	
Threshold Output Power	P _{th}	T _C = -20 to +85°C, I _F = I _{th}		100	200	μW
Optical Output Power	P _o	I _F = I _{th} + 20 mA	4	7		mW
Differential Efficiency	η _d		0.2	0.35		W/A
Temperature Dependence of Differential Efficiency	Δη _d	$\Delta\eta_d = 10 \log \frac{\eta_d (@ 85^\circ\text{C})}{\eta_d (@ 25^\circ\text{C})}$	-3.0	-2.5		dB
Modulation Current	I _{mod}	T _C = 85°C			50	mA
Peak Emission Wavelength	λ _p	P _o = 7.0 mW, RMS (-20 dB), T _C = -20 to +85°C	1 280		1 335	nm
Side Mode Suppression Ratio	SMSR	P _o = 7.0 mW, RMS (-20 dB), T _C = -20 to +85°C	30	45		dB
Vertical Beam Angle ^{*1}	θ _v	P _o = 7.0 mW, FAHM ^{*2}		35	40	deg.
Lateral Beam Angle ^{*1}	θ _l	P _o = 7.0 mW, FAHM ^{*2}		30	35	deg.
Rise Time	t _r	10-90%			0.2	ns
Fall Time	t _f	90-10%			0.2	ns
Monitor Current	I _m	V _R = 5 V, I _F = I _{th} + 20 mA	280	840	1 400	μA
Monitor Dark Current	I _d	V _R = 5 V		0.1	10	nA
		V _R = 5 V, T _C = -20 to +85°C			500	
Monitor PD Terminal Capacitance	C _t	V _R = 5 V, f = 1 MHz		6.0	20	pF
Tracking Error ^{*3}	γ	I _m = const. (@ P _o = 7.0 mW, T _C = 25°C) T _C = -20 to +85°C	-1.0		1.0	dB

*1 Applicable to only NX6307S Series

*2 FAHM: Full Angle at Half Maximum

*3 Tracking Error: γ



$$\gamma = \left| 10 \log \frac{P_o}{7.0} \right| \text{ [dB]}$$

LD CAN PACKAGES FAMILY FOR OPTICAL FIBER COMMUNICATIONS

Part Number	Absolute Maximum Ratings		Electro-Optical Characteristics				Application	Package
			@T _c = 25°C	@T _c				
	T _c (°C)	T _{stg} (°C)	I _{th} (mA)	P _o (mW)	λ (nm)			
			TYP.	TYP.	MIN.	MAX.		
NX5302 Series	-40 to +85	-40 to +85	10	5	1 263	1 360	156 Mb/s: STM-1 (I-1, S-1.1, L-1.1)	CAN
							622 Mb/s: STM-4 (I-4, S-4.1)	
NX5306 Series	-40 to +85	-40 to +85	10	5	1 263	1 360	156 Mb/s: STM-1 (I-1, S-1.1, L-1.1)	CAN
							622 Mb/s: STM-4 (I-4, S-4.1)	
NX5307 Series	-40 to +85	-40 to +85	10	10	1 266	1 360	2.5 Gb/s: STM-16	CAN
NX6301 Series	-40 to +85	-40 to +85	13	5	1 280	1 335	156 Mb/s: STM-1	CAN
							622 Mb/s: STM-4	
NX6306 Series	-40 to +85	-40 to +85	10	5	1 280	1 335	156 Mb/s: STM-1 (I-1, S-1.1, L-1.1)	CAN
							622 Mb/s: STM-4 (I-4, S-4.1, L-4.1)	
NX6307 Series	-20 to +85	-40 to +85	10	7	1 280	1 335	2.5 Gb/s: STM-16 (S-16.1, L-16.1)	CAN
NX6504 Series	-10 to +85	-40 to +85	12	5	1 530	1 570	156 Mb/s: STM-1	CAN
							622 Mb/s: STM-4	

REFERENCE

Document Name	Document No.
OPTICAL SEMICONDUCTOR DEVICES FOR FIBEROPTIC COMMUNICATIONS SELECTION GUIDE	PX10161E
Opto-Electronics Devices Pamphlet	PX10160E
NEC semiconductor device reliability/quality control system ^{*1}	C11159E
Quality grades on NEC semiconductor devices ^{*1}	C11531E
SEMICONDUCTOR SELECTION GUIDE –Products and Packages– ^{*1}	X13769E

*1 Published by NEC Corporation


- **The information in this document is current as of November 2002. The information is subject to change without notice. For actual design-in, refer to the latest publications of NEC's data sheets or data books, etc., for the most up-to-date specifications of NEC semiconductor products. Not all products and/or types are available in every country. Please check with an NEC sales representative for availability and additional information.**
 - No part of this document may be copied or reproduced in any form or by any means without prior written consent of NEC. NEC assumes no responsibility for any errors that may appear in this document.
 - NEC does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from the use of NEC semiconductor products listed in this document or any other liability arising from the use of such products. No license, express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC or others.
 - Descriptions of circuits, software and other related information in this document are provided for illustrative purposes in semiconductor product operation and application examples. The incorporation of these circuits, software and information in the design of customer's equipment shall be done under the full responsibility of customer. NEC assumes no responsibility for any losses incurred by customers or third parties arising from the use of these circuits, software and information.
 - While NEC endeavours to enhance the quality, reliability and safety of NEC semiconductor products, customers agree and acknowledge that the possibility of defects thereof cannot be eliminated entirely. To minimize risks of damage to property or injury (including death) to persons arising from defects in NEC semiconductor products, customers must incorporate sufficient safety measures in their design, such as redundancy, fire-containment, and anti-failure features.
 - NEC semiconductor products are classified into the following three quality grades:
 "Standard", "Special" and "Specific". The "Specific" quality grade applies only to semiconductor products developed based on a customer-designated "quality assurance program" for a specific application. The recommended applications of a semiconductor product depend on its quality grade, as indicated below. Customers must check the quality grade of each semiconductor product before using it in a particular application.
 "Standard": Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots
 "Special": Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support)
 "Specific": Aircraft, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems and medical equipment for life support, etc.
- The quality grade of NEC semiconductor products is "Standard" unless otherwise expressly specified in NEC's data sheets or data books, etc. If customers wish to use NEC semiconductor products in applications not intended by NEC, they must contact an NEC sales representative in advance to determine NEC's willingness to support a given application.
- (Note)
- (1) "NEC" as used in this statement means NEC Corporation, NEC Compound Semiconductor Devices, Ltd. and also includes its majority-owned subsidiaries.
 - (2) "NEC semiconductor products" means any semiconductor product developed or manufactured by or for NEC (as defined above).

M8E 00.4-0110

SAFETY INFORMATION ON THIS PRODUCT



SEMICONDUCTOR LASER



AVOID EXPOSURE-Invisible Laser Radiation is emitted from this aperture

<p>Warning Laser Beam</p>	<p>A laser beam is emitted from this diode during operation. The laser beam, visible or invisible, directly or indirectly, may cause injury to the eye or loss of eyesight.</p> <ul style="list-style-type: none"> • Do not look directly into the laser beam. • Avoid exposure to the laser beam, any reflected or collimated beam.
<p>Caution GaAs Products</p>	<p>The product contains gallium arsenide, GaAs. GaAs vapor and powder are hazardous to human health if inhaled or ingested.</p> <ul style="list-style-type: none"> • Do not destroy or burn the product. • Do not cut or cleave off any part of the product. • Do not crush or chemically dissolve the product. • Do not put the product in the mouth. <p>Follow related laws and ordinances for disposal. The product should be excluded from general industrial waste or household garbage.</p>

► **Business issue**

NEC Compound Semiconductor Devices, Ltd.

5th Sales Group, Sales Division TEL: +81-3-3798-6372 FAX: +81-3-3798-6783 E-mail: salesinfo@csd-nec.com

NEC Compound Semiconductor Devices Hong Kong Limited

Hong Kong Head Office TEL: +852-3107-7303 FAX: +852-3107-7309
 Taipei Branch Office TEL: +886-2-8712-0478 FAX: +886-2-2545-3859
 Korea Branch Office TEL: +82-2-528-0301 FAX: +82-2-528-0302

NEC Electronics (Europe) GmbH <http://www.ee.nec.de/>

TEL: +49-211-6503-01 FAX: +49-211-6503-487

California Eastern Laboratories, Inc. <http://www.cel.com/>

TEL: +1-408-988-3500 FAX: +1-408-988-0279

► **Technical issue**

NEC Compound Semiconductor Devices, Ltd. <http://www.csd-nec.com/>

Sales Engineering Group, Sales Division
 E-mail: techinfo@csd-nec.com FAX: +81-44-435-1918