








500 Notched Spade 14-10 AWG

Spade and Ring Series Uninsulated

STUD	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER	STYLE AND DIMENSIONS
10	.150-.250	✓ ✓	2500	$7/32 \pm 1/32$	.032	Brass	5C3-10	
						Pre Tinned Brass	5C4-10	
1/4	.150-.250	✓ ✓	2500	$7/32 \pm 1/32$	.032	Brass	5C3-12	
						Pre Tinned Brass	5C4-12	
10	None	✓ ✓	2500	$7/32 \pm 1/32$	.032	Brass	5C3-9	
						Pre Tinned Brass	5C4-9	
1/4	None	✓ ✓	2500	$7/32 \pm 1/32$	.032	Brass	5C3-11	
						Pre Tinned Brass	5C4-11	

.240 Notched Spade Insulation Piercing — 2 Barbs

Spade and Ring Series Uninsulated

STUD	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER	STYLE AND DIMENSIONS
0	.075-.125	— —	6000	—	.020	Brass	2E1-0	
						Pre Tinned Brass	2E2-0	
2	.075-.125	— —	6000	—	.020	Brass	2E1-2	
						Pre Tinned Brass	2E2-2	
4	.075-.125	— —	6000	—	.020	Brass	2E1-4	
						Pre Tinned Brass	2E2-4	