Tyco Electronics Our commitment. Your advantage.

• Products

- O By Type
 - Connectors
 - Electromechanical Components
 - Electronic Modules
 - Fiber Optics
 - Filters
 - Identification & Labeling
 - Passive Components
 - Power Sources
 - RF & Microwave Products
 - Tooling Products
 - Touch Screen Displays
 - Tubing, Molded and Harnessing Products
 - Wire, Cable and Cable Assemblies
 - List all product types...
- O <u>By Industry</u>
 - Aerospace & Defense Products
 - Appliance
 - Automotive
 - Communications
 - Computer & Consumer Electronics
 - Industrial & Commercial
 - Instrumentation & Medical
- O By Brand
- O A to Z
- O Product News

Documentation

- O Find Documents & Drawings
- O Find CAD Models
- O SPICE/Electrical Models
- O NAFTA Certificate of Origin
- O White Papers

• Resources

- O RoHS Compliance & Alternates
- O Cross Reference Products
- O Compare Multiple Products
- O Check Distributor Inventory
- O Find Authorized Distributors


• My Account

- O Sign In
- O Register

• Customer Support

- O Support
- O RoHS Support Center

KHU-17D11-48 Product Details



KHU-17D11-48

Active

Mid-Range PC Board Relays



Always EU RoHS compliant but not ELV Compliant (Statement of Compliance)

Product Highlights:

- KHU Series
- Contact Arrangement = 4 Form C, 4PDT, 4 C/O
- Contact Current Rating = 3 Amps.
- Monostable Coil Magnetic System
- Without Coil Suppression Diode

View all Features | Find Similar Products



- Check Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Compare Products
- Contact Us About This Product

Documentation & Additional Information

Product Drawings:

None Available

Catalog Pages/Data Sheets:

• KHA General Purpose Dry Circuit to 5A Multicontact A... (PDF, English)

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

• None Available

CAD Files:

• None Available

Additional Information:

• Product Line Information

Additional Product Images:

- Schematic
- PCB Layout
- Wiring Diagram

Related Products:

• <u>Tooling</u>

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

• <u>Termination Type</u> = Solder Terminals

Electrical Characteristics:

- Contact Current Rating (Amps.) = 3
- <u>Coil Resistance (?)</u> = 2600
- Actuating System = DC
- Coil Power, Nominal (W) = 0.90
- <u>Input Voltage (VDC)</u> = 48

Body Related Features:

- Series = KHU
- Polarized = No

Contact Related Features:

- Mounting Options = PC Board, Socket
- Enclosure = Dust Cover
- FCC Part 68 Isolation = No
- Relay Type = General
- Contact Material = Silver
- Approx. Dimensions (L x W x H) (mm[in]) = 28.20 x 21.80 x 34.90 [1.111 x .858 x 1.375]
- Wiring Diagram= 4 FormC
- Approved Standards = UL Recognized, CSA Certified

Configuration Related Features:

- Contact Arrangement = 4 Form C, 4PDT, 4 C/O
- Coil Magnetic System = Monostable
- <u>Coil Suppression Diode</u> = Without
- <u>Coil Selection Criteria</u> = Nominal Voltage
- Coil Latching = Without
- <u>LED Indicator</u> = Without

Industry Standards:

- RoHS/ELV Compliance = RoHS/Not ELV Compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS not ELV compliant

Other:

Brand = Potter & Brumfield

Provide Website Feedback | Contact Customer Support
Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support
2008 Tyco Electronics Corporation All Rights Reserved