



Lötfreie Kabelschuhe ohne Isolation
Solderless terminals, non insulated

Bauform Supply condition	Artikel-Nummer Part number	DIN 46234	Leiter- querschnitt Wire size mm ² AWG	Bolzen Stud M	Abmessungen mm Dimensions mm						Verp.-Ein. Stück siehe gültige Preisliste
					S	Ø d 1	d 3	L	a	r min	
	RSQ 7180 A 2-0,5	●	0,1-0,5	2	0,5	1,0	5,0	10,0	4,0	5,0	
	RSQ 7180 A 3-0,5	●	26-22	3	0,5	1,0	5,0	10,0	4,0	5,0	
	RSQ 7181 A 3,5-0,5	●		3,5	0,5	1,0	6,5	12,0	4,0	5,0	
	RSQ 7181 A 4-0,5	●		4	0,5	1,0	6,5	12,0	4,0	6,0	
	RSQ 7103 A 3-1	●	0,25-1,5	3	0,8	1,6	6,0	10,8	4,8	4,5	
	RSQ 7103 A 3,5-1	●	22-16	3,5	0,8	1,6	6,0	10,8	4,8	4,5	
	RSQ 7104 A 4-1	●		4	0,8	1,6	8,0	11,8	4,8	6,0	
	RSQ 7105 A 5-1	●		5	0,8	1,6	10,0	12,8	4,8	6,5	
	RSQ 7105 A 6-1	●		6	0,8	1,6	10,0	12,8	4,8	6,5	
	RSQ 7158 A 6-1	●		6	0,8	1,6	11,0	14,8	4,8	7,5	
RSQ 7158 A 8-1	●		8	0,8	1,6	11,0	14,8	4,8	7,5		
RSQ 7159 A 3-2,5	●	>1-2,5	3	0,8	2,3	6,0	10,8	4,8	4,5		
RSQ 7159 A 3,5-2,5	●	16-14	3,5	0,8	2,3	6,0	10,8	4,8	4,5		
RSQ 7108 A 4-2,5	●		4	0,8	2,3	8,0	11,8	4,8	6,0		
RSQ 7108 A 5-2,5	●		5	0,8	2,3	8,0	11,8	4,8	6,0		
RSQ 7109 A 5-2,5	●		5	0,8	2,3	10,0	13,6	4,8	6,5		
RSQ 7110 A 6-2,5	●		6	0,8	2,3	11,0	13,8	4,8	7,5		
RSQ 7162 A 8-2,5	●		8	0,8	2,3	14,0	17,0	5,0	10,0		
RSQ 7151 A 10-2,5	●		10	0,8	2,3	18,0	20,0	5,0	12,0		
RSQ 7155 A 4-6	●	>2,5-6	4	1,0	3,6	8,0	14,0	6,0	6,0		
RSQ 7112 A 5-6	●	12-10	5	1,0	3,6	10,0	15,0	6,1	6,5		
RSQ 7114 A 6-6	●		6	1,0	3,6	11,0	16,0	6,1	7,5		
RSQ 7115 A 8-6	●		8	1,0	3,6	14,0	19,0	6,1	10,0		
RSQ 7117 A 10-6	●		10	1,0	3,6	18,0	21,0	6,0	12,0		
RSQ 7119 A 4-10	●	>6-10	4	1,1	4,5	10,0	16,0	8,0	6,5		
RSQ 7119 A 5-10	●	8	5	1,1	4,5	10,0	16,0	8,0	6,5		
RSQ 7120 A 6-10	●		6	1,1	4,5	11,0	17,0	8,0	7,5		
RSQ 7121 A 8-10	●		8	1,1	4,5	14,0	20,0	8,0	10,0		
RSQ 7122 A 10-10	●		10	1,1	4,5	18,0	21,0	8,0	12,0		
RSQ 7123 A 12-10	●		12	1,1	4,5	22,0	23,0	8,0	13,0		
RSQ 7125 A 5-16	●	>10-16	5	1,2	5,8	11,0	20,0	10,0	7,5		
RSQ 7125 A 6-16	●	6	6	1,2	5,8	11,0	20,0	10,0	7,5		
RSQ 7126 A 8-16	●		8	1,2	5,8	14,0	22,0	10,0	10,0		
RSQ 7127 A 10-16	●		10	1,2	5,8	18,0	24,0	10,0	12,0		
RSQ 7128 A 12-16	●		12	1,2	5,8	22,0	26,0	10,0	13,0		

Material: SE-Cu, galv. verzinkt
 Material: electrolytic copper, electro-tinned

Lötfreie Kabelschuhe ohne Isolation
Solderless terminals, non insulated

Bauform Supply condition	Artikel-Nummer Part number	DIN 46234	Leiter- querschnitt Wire size mm ² AWG	Bolzen Stud M	Abmessungen mm Dimensions mm						Verp.-Einh. Stück siehe gültige Preisliste
					S	Ø d 1	d 3	L	a	r	
	RSQ 7156 A 6-25	●	>16-25	5	1,5	7,5	12,0	25,0	11,0	7,5	
	RSQ 7130 A 8-25	●	4	6	1,5	7,5	12,0	25,0	11,0	7,5	
	RSQ 7131 A 10-25	●		8	1,5	7,5	16,0	25,0	11,0	10,0	
	RSQ 7132 A 12-25	●		10	1,5	7,5	18,0	26,0	11,0	12,0	
	RSQ 7132 A 12-25	●		12	1,5	7,5	22,0	31,0	11,0	13,0	
	RSQ 7229 A 6-35	●	>25-35	6	1,6	9,0	15,0	26,0	12,0	10,0	
	RSQ 7134 A 8-35	●	2	8	1,6	9,0	16,0	26,0	12,0	10,0	
	RSQ 7175 A 10-35	●		10	1,6	9,0	18,0	27,0	12,0	12,0	
	RSQ 7135 A 12-35	●		12	1,6	9,0	22,0	31,0	12,0	13,0	
	RSQ 7212 A 16-35	●		16	1,6	9,0	28,0	36,0	12,0	16,0	
RSQ 7136 A 6-50	●	>35-50	6	1,8	11,0	18,0	34,0	16,0	12,0		
RSQ 7136 A 8-50	●	1/0	8	1,8	11,0	18,0	34,0	16,0	12,0		
RSQ 7136 A 10-50	●		10	1,8	11,0	18,0	34,0	16,0	12,0		
RSQ 7137 A 12-50	●		12	1,8	11,0	22,0	36,0	16,0	13,0		
RSQ 7139 A 16-50	●		16	1,8	11,0	28,0	40,0	16,0	16,0		
RSQ 7140 A 6-70	●	>50-70	6	2,0	13,0	22,0	38,0	18,0	13,0		
RSQ 7140 A 8-70	●	2/0	8	2,0	13,0	22,0	38,0	18,0	13,0		
RSQ 7140 A 10-70	●		10	2,0	13,0	22,0	38,0	18,0	13,0		
RSQ 7140 A 12-70	●		12	2,0	13,0	22,0	38,0	18,0	13,0		
RSQ 7142 A 16-70	●		16	2,0	13,0	28,0	42,0	18,0	16,0		
RSQ 7144 A 8-95	●	>70-95	8	2,5	15,0	24,0	42,0	20,0	13,0		
RSQ 7144 A 10-95	●	3/0	10	2,5	15,0	24,0	42,0	20,0	13,0		
RSQ 7144 A 12-95	●		12	2,5	15,0	24,0	42,0	20,0	13,0		
RSQ 7145 A 16-95	●		16	2,5	15,0	28,0	44,0	20,0	16,0		
RSQ 7146 A 8-120	●	>95-120	8	3,0	16,5	24,0	44,0	22,0	13,0		
RSQ 7146 A 10-120	●	4/0	10	3,0	16,5	24,0	44,0	22,0	13,0		
RSQ 7146 A 12-120	●		12	3,0	16,5	24,0	44,0	22,0	13,0		
RSQ 7147 A 16-120	●		16	3,0	16,5	28,0	48,0	22,0	16,0		
RSQ 7149 A 10-150	●	>120-150	10	3,2	19,0	30,0	50,0	24,0	16,0		
RSQ 7149 A 12-150	●	250-300	12	3,2	19,0	30,0	50,0	24,0	16,0		
RSQ 7149 A 16-150	●	MCM	16	3,2	19,0	30,0	50,0	24,0	16,0		
RSQ 7172 A 10-185	●	>150-185	10	3,5	21,0	36,0	50,0	28,0	16,0		
RSQ 7172 A 12-185	●	300-350	12	3,5	21,0	36,0	50,0	28,0	16,0		
RSQ 7172 A 16-185	●	MCM	16	3,5	21,0	36,0	50,0	28,0	16,0		
RSQ 7173 A 10-240	●	>185-240	10	4,0	23,5	38,0	56,0	32,0	16,0		
RSQ 7173 A 12-240	●	350-450	12	4,0	23,5	38,0	56,0	32,0	16,0		
		MCM									
RSQ 7174 A 12-300		>240-300	12	4,5	27,5	50,0	69,0	35,0	16,0		
		500-600									
		MCM									

Material: SE-Cu. galv. verzinkt
 Material: electrolytic copper, electro-tinned