

500 mW DO-35 Hermetically Sealed Glass Zener Voltage Regulators



Absolute Maximum Ratings $T_A = 25^\circ\text{C}$ unless otherwise noted



Parameter	Value	Units
Power Dissipation	500	mW
Storage Temperature Range	-65 to +200	$^\circ\text{C}$
Operating Junction Temperature	+200	$^\circ\text{C}$
Lead Temperature (1/16" from case for 10 seconds)	+230	$^\circ\text{C}$

These ratings are limiting values above which the serviceability of the diode may be impaired.

Specification Features:

- Zener Voltage Range 3.3 to 12 Volts
- DO-35 Package (JEDEC)
- Through-Hole Device Type Mounting
- Hermetically Sealed Glass
- Compression Bonded Construction
- All external surfaces are corrosion resistant and leads are readily solderable
- Cathode indicated by polarity band

DEVICE MARKING DIAGRAM



ELECTRICAL SYMBOL

Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise noted

Device Type	$V_Z @ I_{ZT}$ (Volts) Nominal	I_{ZT} (mA)	$Z_{ZT} @ I_{ZT}$ (Ω) Max	$I_R @ V_R$ (μA) Max	V_R (Volt)
TC1N746A	3.3	20	28	10	1
TC1N747A	3.6	20	24	10	1
TC1N748A	3.9	20	23	10	1
TC1N749A	4.3	20	22	2	1
TC1N750A	4.7	20	19	2	1
TC1N751A	5.1	20	17	1	1
TC1N752A	5.6	20	11	1	1
TC1N753A	6.2	20	7	0.1	1
TC1N754A	6.8	20	5	0.1	1
TC1N755A	7.5	20	6	0.1	1
TC1N756A	8.2	20	8	0.1	1
TC1N757A	9.1	20	10	0.1	1
TC1N758A	10	20	17	0.1	1
TC1N759A	12	20	30	0.1	1


V_F Forward Voltage = 1.5 V Maximum @ $I_F = 200$ mA for all types

Notes:

1. The type numbers listed have zener voltage as shown and have a standard tolerance on the nominal zener voltage of $\pm 5\%$. Suffix (BLANK) = $\pm 10\%$, Suffix C = $\pm 2\%$ and D = $\pm 1\%$.
2. For detailed information on price, availability and delivery of nominal zener voltages between the voltages shown and tighter voltage tolerances, contact your nearest Tak Cheong Electronics representative.
3. The zener impedance is derived from the 60-cycle ac voltage, which results when an ac current having an rms value equal to 10% of the dc zener current (I_{ZT}) is superimposed to I_{ZT} .

Electrical Symbol Definition

Symbol	Parameter
V_Z	Reverse Zener Voltage @ I_{ZT}
I_{ZT}	Reverse Current
Z_{ZT}	Maximum Zener Impedance @ I_{ZT}
I_{ZK}	Reverse Current
Z_{ZK}	Maximum Zener Impedance @ I_{ZK}
I_R	Reverse Leakage Current @ V_R
V_R	Breakdown Voltage
I_F	Forward Current
V_F	Forward Voltage @ I_F

Typical Characteristics

Ordering Information


Device	Package	Quantity
TC1N7xxA	Bulk	10,000
TC1N7xxA.TB	Tape and Ammo (52mm)	5,000
TC1N7xxA.TR	Tape and Reel (52mm)	10,000
TC1N7xxA.TB26	Tape and Ammo (26mm)	5,000
TC1N7xxA	Others (...contact Tak Cheong sales representatives)	

Axial-Lead Tape Packaging Standards


This axial-lead component's packaging requirements use in automatic testing and assembly equipment. And this standard practices for lead-tape packaging of axial-lead components meets the requirements of EIA Standard RS-296-D "Lead-taping of Components on Axial Lead Configuration for Automatic Insertion".

Tape & Reel Packaging Information

Tape & Reel Outline




Reel Dimensions



DIM	Millimeters
D1	356
D2	30
D3	84
W1	77.5

Quantity Per Reel

PKG Type	Quantity Per Reel
DO-35	10,000


Tape & Ammo Packaging Information
Tape & Ammo Outline


FOR 52mm BOX
250mm x 80mm x 80mm

FOR 26mm BOX
255mm x 100mm x 48mm

Quantity Per Ammo Box


PKG Type	Quantity Per Box
DO-35	5,000

Taping Dimensions


Description	Millimeters	
Standard Width	52	26
Tape Spacing (B)	52.37 ± 1.5	26 ± 1.5
Component Pitch (C)	5.08 ± 0.4	5.08 ± 0.4
Untaped Lead (L1 – L2)	± 1.4	± 1.0
Glass Offset (F)	± 0.79	± 0.79
Bent (D)	1.2 Max	1.2 Max
Tape Width (G)	6.138 ± 0.576	6.138 ± 0.576
Tape Mismatch (E)	0.75 Max	0.75 Max
Taped Lead (G)	2 Min	2 Min
Lead Beyond Tape (H)	0	0

Bulk Packaging Information


Bulk Outline



Quantity Per Box

PKG Type	Quantity Per Box
DO-35	10,000

Package Outline

Package	Case Outline				
DO-35					
	DIM	DO-35			
		Millimeters		Inches	
		Min	Max	Min	Max
	A	0.46	0.55	0.018	0.022
	B	3.05	5.08	0.120	0.200
	C	25.40	38.10	1.000	1.500
	D	1.53	2.28	0.060	0.090

Notes:

1. All dimensions are within JEDEC standard.
2. DO35 polarity denoted by cathode band.