







Mounting hole
patterns
for standard



Vertical Mount PCB Jack (Top Entry)



No.of Positions	Dimensions			
	A	B	C	D
4	<u>13.97</u> .550	<u>11.43</u> .450	<u>7.62</u> .300	<u>3.81</u> .150
6	<u>16.00</u> .630	<u>13.46</u> .530	<u>10.16</u> .400	<u>6.35</u> .250
8	<u>17.84</u> .700	<u>15.36</u> .605	<u>11.80</u> .465	<u>8.89</u> .350

Materials

- **Housing:** Standard Material Glass Filled Polyester UL 94V-0
Standard Color Black
- **Contact:** 0.46mm (0.018") Diameter Alloy C5210 Gold Plating Over Nickel.
- **Gold Plating:** As Per Customer Request.

Ordering Information

Positions / Contacts	Description	W / Flange	Flangeless
4P2C	Vertical Mount	303042V	303042VFL
4P4C	Vertical Mount	303044V	303044VFL
6P2C	Vertical Mount	303062V	303062VFL
6P4C	Vertical Mount	303064V	303064VFL
6P6C	Vertical Mount	303066V	303066VFL
8P8C	Vertical Mount	303068V	303068VFL

Standard contact plating is 15 micro inches of gold. For optional platings add dash number as follows:

- 6 = 6 Micro inches
- 30 = 30 Micro inches
- 50 = 50 Micro inches