

[Home](#) > [Products](#) > [By Type](#) > [Relays](#) > [Product Feature Selector](#) > Product Details

7012AFGZL Product Details



Time Delay Relays

[Not EU RoHS or ELV Compliant](#)

Product Highlights:

- 7000 Electropneumatic Timing - Industrial Series
- Input Voltage = 110 VAC, 120 VAC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Rating = 10A @ 240 VAC
- Mounting Options = Panel Mount

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

7012AFGZL
(1-1423157-6)
TE Internal Number: 1-1423157-6

 **Active**

 [Add to My Part List](#)

 [Request Sample](#)

 [Find Similar Products](#)

 [Buy Product](#)

Documentation & Additional Information	
Product Drawings: - None Available Catalog Pages/Data Sheets: - None Available Product Specifications: - None Available Application Specifications: - None Available Instruction Sheets: - None Available CAD Files: - None Available List all Documents	Additional Information: Product Line Information Related Products: Tooling
Product Features (Please use the Product Drawing for all design activity)	
Product Type Features: - Termination Type = Screw Terminal Electrical Characteristics: - Input Voltage (VAC) = 110, 120 - Contact Rating = 10A @ 240 VAC Body Related Features: - Series = 7000 Electropneumatic Timing - Industrial Contact Related Features: - Mounting Options = Panel Mount - Mode of Operation = On-Delay - Delay Time = 1 minute to 10 minutes - Type of Control = Knob - Repeatability, Max. = ± 10% - Approved Standards = CE Approved, CSA Certified, FM Approved, UL Listed - Option = Auxiliary Switch - Instant Transfer, Enclosure with Bottom Knockouts - Approx. Dimensions (L x W x H) (mm [in]) = 114.80 x 65.30 x 71.90 [4.523 x 2.572 x 2.832]	Configuration Related Features: Contact Arrangement = 2 Form C, DPDT, 2 C/O - Multiple Timing Ranges = Without Industry Standards: RoHS/ELV Compliance = Not ELV/RoHS compliant Lead Free Solder Processes = Not relevant for lead free process Conditions for Usage: - Temperature Range (?C) = -30 - +75 Other: - Brand = Agastat

Corporate Information

[Who We Are](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)

Quick Links

[Check Distributor Inventory](#)
[Cross Reference](#)
[Find Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat with Us](#)
[Find a Phone Number](#)
[Search Knowledge Base](#)
[Manage Your Account](#)