

FETs for LF Amp General-purpose Amp, Differential Amp Applications

Marking: Numeral for Type No. For PNP, (-) sign is omitted.

Case Outline(unit:mm)


SANYO:CP5

Technical drawing of the SANYO:CP5 case outline. The drawing includes a top view, a side view, and a detail view of the mounting tab. The top view shows a rectangular case with a width of 2.9 mm and a height of 2.8 mm. The mounting tab has a width of 0.6 mm and a height of 0.5 mm. The distance between the mounting tabs is 1.9 mm. The side view shows a thickness of 0.6 mm. The detail view shows a mounting tab with a width of 0.16 mm and a height of 0.1 mm.


ANYO:CP6

Technical drawing of the ANYO:CP6 case outline. The drawing includes a top view, a side view, and a detail view of the mounting tab. The top view shows a rectangular case with a width of 2.9 mm and a height of 2.8 mm. The mounting tab has a width of 0.6 mm and a height of 0.5 mm. The distance between the mounting tabs is 1.9 mm. The side view shows a thickness of 0.6 mm. The detail view shows a mounting tab with a width of 0.16 mm and a height of 0.1 mm.


FC12, FC15, FC18



FC13




FC14




Diodes for High-speed Switching Applications

Marking: Numeral for Type No.


FC807




FC601




FC808




FC804, FC805, FC806, FC809, FC810, 1SV241, 1SV265



FC801



FC802, FC803



MT941226TR