

1SS174

Silicon Schottky Barrier Diode for UHF TV Tuner Mixer, Various Detector,
High Speed Switching


Features

- Low capacitance.(C=1.2pF max)
- Small glass package (MHD) enables easy mounting and high reliability.

Ordering Information

Type No.	Cathode band	Mark	Package Code
1SS174	Green	1	MHD

Outline



Absolute Maximum Ratings (Ta = 25°C)

Item	Symbol	Value	Unit
Reverse voltage	V_R	3	V
Average forward current	I_o	30	mA
Power dissipation	P_d	150	mW
Junction temperature	T_j	100	°C
Storage temperature	T_{stg}	-55 to +100	°C

Electrical Characteristics (Ta = 25°C)

Item	Symbol	Min	Typ	Max	Unit	Test Condition
Forward current	I_F	35	—	—	mA	$V_F = 0.5 \text{ V}$
Reverse voltage	V_R	3	—	—	V	$I_R = 1 \text{ mA}$
Reverse current	I_R	—	—	50	μA	$V_R = 0.5 \text{ V}$
Capacitance	C	—	—	1.2	pF	$V_R = 0.5 \text{ V}, f = 1 \text{ MHz}$
ESD-Capability	—	30	—	—	V	*C=200pF, Both forward and reverse direction 1 pulse.

* Failure criterion ; $I_R \geq 50 \mu\text{A}$




Fig.1 Forward current Vs. Forward voltage




Fig.2 Reverse current Vs. Reverse voltage




Fig.3 Capacitance Vs. Reverse voltage