


Ultrasonic proximity sensors

UNAM 18 (with Teach-in)

sample drawing



general data

scanning range sd	100 ... 1000 mm
scanning range far limit Sde	100 ... 1000 mm
hysteresis typ.	4 % Sde
repeat accuracy	< 0,5 mm
temperature drift	< 0,18 % Sde/K
response time ton	< 50 ms
release time toff	< 50 ms
alignment aid	target indication flashing
sonic frequency	240 kHz
output indicator	LED green
adjustment	Teach-in

electrical data

voltage supply range +Vs	12 ... 30 VDC
current consumption max.	35 mA
output current	< 200 mA
voltage drop Vd	< 2 VDC
residual ripple	< 10 % Vs
short circuit protection	yes
reverse polarity protection	yes

mechanical data

width / diameter	18 mm
height / length	90 mm
connection types	connector M12
type	cylindrical
housing material	brass nickel plated

ambient conditions

operating temperature	-10 ... +60 °C
protection class	IP 67

sample picture



Ultrasonic proximity sensors

UNAM 18 (with Teach-in)

order reference	output circuit
UNAM 18N6903/S14	NPN make function (NO)
UNAM 18N7903/S14	NPN break function (NC)
UNAM 18P6903/S14	PNP make function (NO)
UNAM 18P7903/S14	PNP break function (NC)