



(1.14)±.045 SQ. OR ROUND PIN IS STANDARD. HOUSING WILL ACCEPT PIN SIZES FROM (.51)±.020 TO (1.37)±.062

EXLT. NO. 1 (SEE NOTE 3)

209-NP-4

NO. OF CRT'S.

OPT. CODE	RAMP	POL. RIB EARS	MATERIAL	ENGRAVING
A	STD. RAMP	NO	NYLON 94V-2	STD.
C	NONE	NO	NYLON 94V-2	STD.
D	STD. RAMP	NO	NYLON 94V-0	STD.
F	NONE	NO	NYLON 94V-0	STD.
G	WIDE RAMP	NO	NYLON 94V-2	STD.
H				
J				
K				
L	STD. RAMP	NO	NYLON 6 94V-2	STD.
N	NONE	NO	NYLON 6 94V-2	STD.
P	STD. RAMP	YES	NO. NYLON 94V-2	STD.

SELECTIVE RAMP LOC.
BLANK-NONE
SEL. SEL. LOC.
AD-2NG. SEL. LOC., ETC.

VOID CODE
NO. CORRESPONDS TO
MULT. VOIDS START WITH 5.

COLOR CODE
BLANK-NATURAL
GR-GRN
OR-RED
OR-ORANGE
BU-BLUE
BK-BLACK

NO. OF	DIM. B	DIM. A
2	(7.82)	(3.96±.13)
3	(11.79)	(7.92±.13)
4	(15.75)	(11.69±.13)
5	(19.71)	(15.65±.13)
6	(23.67)	(19.61±.13)
7	(27.64)	(23.57±.13)
8	(31.60)	(27.53±.13)
9	(35.56)	(31.49±.13)
10	(39.52)	(35.45±.13)
11	(43.48)	(39.41±.13)
12	(47.44)	(43.37±.13)
13	(51.40)	(47.33±.13)
14	(55.36)	(51.29±.13)
15	(59.32)	(55.25±.13)
16	(63.28)	(59.21±.13)
17	(67.24)	(63.17±.13)
18	(71.20)	(67.13±.13)
19	(75.16)	(71.09±.13)
20	(79.12)	(75.05±.13)
21	(83.08)	(79.01±.13)
22	(87.04)	(82.97±.13)
23	(91.00)	(86.93±.13)
24	(94.96)	(90.89±.13)

NO.	DESCRIPTION	REV.	DATE
1	INITIAL RELEASE	1.0	10/16/00
2	REVISED TO ADD DIMENSIONS	1.1	10/16/00
3	REVISED TO ADD DIMENSIONS	1.2	10/16/00
4	REVISED TO ADD DIMENSIONS	1.3	10/16/00
5	REVISED TO ADD DIMENSIONS	1.4	10/16/00
6	REVISED TO ADD DIMENSIONS	1.5	10/16/00
7	REVISED TO ADD DIMENSIONS	1.6	10/16/00
8	REVISED TO ADD DIMENSIONS	1.7	10/16/00
9	REVISED TO ADD DIMENSIONS	1.8	10/16/00
10	REVISED TO ADD DIMENSIONS	1.9	10/16/00
11	REVISED TO ADD DIMENSIONS	2.0	10/16/00
12	REVISED TO ADD DIMENSIONS	2.1	10/16/00
13	REVISED TO ADD DIMENSIONS	2.2	10/16/00
14	REVISED TO ADD DIMENSIONS	2.3	10/16/00
15	REVISED TO ADD DIMENSIONS	2.4	10/16/00
16	REVISED TO ADD DIMENSIONS	2.5	10/16/00
17	REVISED TO ADD DIMENSIONS	2.6	10/16/00
18	REVISED TO ADD DIMENSIONS	2.7	10/16/00
19	REVISED TO ADD DIMENSIONS	2.8	10/16/00
20	REVISED TO ADD DIMENSIONS	2.9	10/16/00
21	REVISED TO ADD DIMENSIONS	3.0	10/16/00
22	REVISED TO ADD DIMENSIONS	3.1	10/16/00
23	REVISED TO ADD DIMENSIONS	3.2	10/16/00
24	REVISED TO ADD DIMENSIONS	3.3	10/16/00

NOTES:

- THIS HOUSING FOR USE WITH TERMINAL NO. 2478 (18 TO 24 GA) & 2578 (22 TO 26 GA), WITH (2.54)±.100 MAX INSULATION DIA. HOUSING 41695 IS RECOMMENDED FOR OVER (2.54)±.100 DIA. INSULATION.
- DIMENSIONS GIVEN ACROSS CENTERLINES ARE SYMMETRICAL ABOUT THOSE CENTERLINES WITHIN HALF THE TOTAL TOLERANCE.
- FIRST CRT. NO. ON 1 THRU 5 CRT. HOUSINGS. FIRST AND LAST CRT. NO. ON 6 CRT. HOUSINGS AND LARGER.
- MAX BOW .005 MM/MMA OR .005 IN/IN
- PARTS CONFORM TO PRODUCT SPECIFICATION PS-08-90.
- 2139-NP-4 IN MANUFACTURED IN SINGAPORE ONLY

