








Connector	Micro	Micro	Micro	Micro
Style	4 Pin DC / 3 Pin AC	4 Pin DC / 3 Pin AC	4 Pin DC / 3 Pin AC	4 Pin DC / 3 Pin AC
Configuration	Straight Female	Right Female	Straight Male	Right Male
    				
	Part Number	Part Number	Part Number	Part Number
DC	BKS-S19F-IN-LINE	BKS-S20F-IN-LINE	BKS-S19M-IN-LINE	BKS-S20M-IN-LINE
AC	BKS-S21F-IN-LINE	BKS-S22F-IN-LINE	BKS-S21M-IN-LINE	BKS-S22M-IN-LINE
Operating Voltage Rating	DC=150VDC/AC=250VAC			
Amperage	4 A			
Max. Wire Gauge	18 AWG			
Housing Material	PA 6.6			
Coupling Nut	Nickel Plated Brass			
Protection	IP 67			
Terminals	Screw Terminals			
Cable Diameter	2...6mm			

Connector	Nano	Nano
Style	3 Pin DC	3 Pin DC
Configuration	Straight Female	Straight Male
 		
	Part Number	Part Number
DC	BKS-S48-FEMALE-IN-LINE	BKS-S48M-IN-LINE
Operating Voltage Rating	DC=150VDC/AC=250VAC	
Amperage	4A	
Max. Wire Gauge	18 AWG	
Housing Material	PA 6.6	
Coupling Nut	Nickel Plated Brass	
Protection	IP 67	
Terminals	Solder Lug for 20AWG	