



Powerex, Inc., Hillis Street, Youngwood, Pennsylvania 15697 (412) 925-7272

Powerex Europe, S.A., 428 Avenue G. Durand, BP107, 72003 Le Mans, France (43) 41.14.14

REVERSE CONDUCTING GTO THYRISTORS

Type	V _{DRM} Volts	V _{D(OC)} Volts	I _{DRM} mA	I _{TORM} Amperes	C _s (μF)	I _{TRMS} Amperes	I _{RRMS} Amperes	I _{TSM} Amperes	I _{TRSM} Amperes	I _{TH} A ² s	I _{RH} A ² s
FGR2000BH40	2000	1600	150	2000	4.0	1100	1100	10400	10400	4.5 x 10 ⁵	3.4 x 10 ⁵
FGR2000BH50	2500	2000	150	2000	4.0	1100	1100	10400	10400	4.5 x 10 ⁵	3.4 x 10 ⁵
FGR2000BV70	3500	2800	150	2000	4.0	940	940	9000	9000	3.4 x 10 ⁵	3.4 x 10 ⁵
FGR2000BV80	4000	3200	150	2000	4.0	940	940	9000	9000	3.4 x 10 ⁵	3.4 x 10 ⁵
FGR2000BV90	4500	3600	150	2000	4.0	940	940	9000	9000	3.4 x 10 ⁵	3.4 x 10 ⁵
FGR3000AH40	2000	1600	200	3000	6.0	1155	1000	15000	15000	9.4 x 10 ⁵	9.4 x 10 ⁵
FGR3000AH50	2500	2000	200	3000	6.0	1155	1000	15000	15000	9.4 x 10 ⁵	9.4 x 10 ⁵
FGR3000AV70	3500	2800	200	3000	6.0	1000	860	14000	14000	8.2 x 10 ⁵	8.2 x 10 ⁵
FGR3000AV80	4000	3200	200	3000	6.0	1000	860	14000	14000	8.2 x 10 ⁵	8.2 x 10 ⁵
FGR3000AV90	4500	3600	200	3000	6.0	1000	860	14000	14000	8.2 x 10 ⁵	8.2 x 10 ⁵

*At 1570A

**At 3000A

GTO MODULES

Type	Also Available As:	V _{DRM} Volts	V _{D(OC)} Volts	I _{DRM} mA	I _{TORM} Amperes	C _s (μF)	I _{TRMS} Amperes	I _{TSM} Amperes	I _{TH} A ² s
GM100DY16	GDM20810	800	640	10	100	0.1	30	400	6.7 x 10 ²
GM100DY20	GDM21010	1000	800	10	100	0.1	30	400	6.7 x 10 ²
GM100DY24	GDM21210	1200	960	10	100	0.1	30	400	6.7 x 10 ²
GM200DY16	GDM20820	800	640	30	200	0.47	70	500	1.0 x 10 ³
GM200DY20	GDM21020	1000	800	30	200	0.47	70	500	1.0 x 10 ³
GM200DY24	GDM21220	1200	960	30	200	0.47	70	500	1.0 x 10 ³

GTO Pow-R-Brik™

Type	V _{DRM} Volts	V _{D(OC)} Volts	I _{DRM} mA	I _{TORM} Amperes	C _s (μF)	I _{TRMS} Amperes	I _{TSM} Amperes	I _{TH} A ² s
P5ZAAGT118W25	2500	2000	50	1800	4.0	700	11000	5.1 x 10 ⁵

V_{TM} (at I_{TQRM}) Volts	V_{RM} Volts	I_{GT} mA	V_{GT} Volts	t_{gt} μs	t_{gq} μs	di_T/dt A/ μs	dv/dt V/ μs	$R_{\theta JS}$ GTO part $^{\circ}C/W$	$R_{\theta JS}$ Diode part $^{\circ}C/W$	Mounting Force (kN)	Outline Drawings	
											Number	Page
3.5	2.5*	3000	1.5	10	30	300	1000	0.023	0.032	36.0 to 44.0	12	16
3.5	2.5*	3000	1.5	10	30	300	1000	0.023	0.032	36.0 to 44.0	12	16
4.4	3.0*	3000	1.5	10	30	300	1000	0.023	0.032	36.0 to 44.0	12	16
4.4	3.0*	3000	1.5	10	30	300	1000	0.023	0.032	36.0 to 44.0	12	16
4.4	3.0*	3000	1.5	10	30	300	1000	0.023	0.032	36.0 to 44.0	12	16
3.5	4.0**	4000	3.0	10	30	500	1500	0.020	0.030	40.0 to 54.0	15	17
3.5	4.0**	4000	3.0	10	30	500	1500	0.020	0.030	40.0 to 54.0	15	17
4.0	4.5**	4000	3.0	10	30	500	1500	0.020	0.030	40.0 to 54.0	15	17
4.0	4.5**	4000	3.0	10	30	500	1500	0.020	0.030	40.0 to 54.0	15	17
4.0	4.5**	4000	3.0	10	30	500	1500	0.020	0.030	40.0 to 54.0	15	17

V_{TM} (at I_{TQRM}) Volts	I_{GT} mA	V_{GT} Volts	t_{gt} μs	t_{gq} μs	di_T/dt A/ μs	dv/dt V/ μs	$R_{\theta JC}$ GTO part $^{\circ}C/W$	$R_{\theta JC}$ Diode part $^{\circ}C/W$	Mounting Torque (N.m)	Outline Drawings	
										Number	Page
4.5	400	1.5	4	8	200	1000	0.7	0.6	2.0 to 3.0	17	18
4.5	400	1.5	4	8	200	1000	0.7	0.6	2.0 to 3.0	17	18
4.5	400	1.5	4	8	200	1000	0.7	0.6	2.0 to 3.0	17	18
4.3	900	1.5	4	10	200	1000	0.35	0.6	2.0 to 3.0	18	18
4.3	900	1.5	4	10	200	1000	0.35	0.6	2.0 to 3.0	18	18
4.3	900	1.5	4	10	200	1000	0.35	0.6	2.0 to 3.0	18	18

V_{TM} (at I_{TQRM}) Volts	I_{GT} mA	V_{GT} Volts	t_{gt} μs	t_{gq} μs	di_T/dt A/ μs	dv/dt V/ μs	$R_{\theta JC}$ GTO part $^{\circ}C/W$	$R_{\theta JC}$ Diode part $^{\circ}C/W$	Mounting Torque (N.m)	Outline Drawings	
										Number	Page
2.6	4000	2.0	10	30	300	500	.048	.050	—	19	18