





- ▼ Simple Drive Requirement
- ▼ Good Thermal Performance
- ▼ Fast Switching Performance
- ▼ RoHS Compliant



N-CH	BV_{DSS}	40V
	$R_{DS(ON)}$	36m Ω
	I_D	11.7A
P-CH	BV_{DSS}	-40V
	$R_{DS(ON)}$	72m Ω
	I_D	-8.7A

Description

The Advanced Power MOSFETs from APEC provide the designer with the best combination of fast switching, ruggedized device design, low on-resistance and cost-effectiveness.



Absolute Maximum Ratings

Symbol	Parameter	Rating		Units
		N-channel	P-channel	
V_{DS}	Drain-Source Voltage	40	-40	V
V_{GS}	Gate-Source Voltage	± 16	± 20	V
$I_D @ T_C = 25^\circ C$	Continuous Drain Current ³	11.7	-8.7	A
$I_D @ T_C = 100^\circ C$	Continuous Drain Current ³	7.4	-5.5	A
I_{DM}	Pulsed Drain Current ¹	50	-40	A
$P_D @ T_C = 25^\circ C$	Total Power Dissipation	9		W
	Linear Derating Factor	0.07		W/ $^\circ C$
T_{STG}	Storage Temperature Range	-55 to 150		$^\circ C$
T_J	Operating Junction Temperature Range	-55 to 150		$^\circ C$

Thermal Data

Symbol	Parameter	Value	Unit
Rthj-c	Thermal Resistance Junction-case ³	Max. 14	$^\circ C/W$
Rthj-a	Thermal Resistance Junction-ambient ³	Max. 110	$^\circ C/W$



N-CH Electrical Characteristics @T_j=25°C(unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250uA	40	-	-	V
ΔBV _{DSS} /ΔT _j	Breakdown Voltage Temperature Coefficient	Reference to 25°C, I _D =1mA	-	0.03	-	V/°C
R _{DS(ON)}	Static Drain-Source On-Resistance ²	V _{GS} =10V, I _D =8A	-	-	36	mΩ
		V _{GS} =4.5V, I _D =6A	-	-	42	mΩ
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250uA	0.8	-	2.5	V
g _{fs}	Forward Transconductance	V _{DS} =10V, I _D =8A	-	8	-	S
I _{DSS}	Drain-Source Leakage Current (T _j =25°C)	V _{DS} =40V, V _{GS} =0V	-	-	1	uA
	Drain-Source Leakage Current (T _j =70°C)	V _{DS} =32V, V _{GS} =0V	-	-	25	uA
I _{GSS}	Gate-Source Leakage	V _{GS} =±16V	-	-	±30	uA
Q _g	Total Gate Charge ²	I _D =8A V _{DS} =30V V _{GS} =4.5V	-	7.4	12	nC
Q _{gs}	Gate-Source Charge		-	1.6	-	nC
Q _{gd}	Gate-Drain ("Miller") Charge		-	3.5	-	nC
t _{d(on)}	Turn-on Delay Time ²	V _{DS} =20V	-	5.3	-	ns
t _r	Rise Time	I _D =8A	-	19.3	-	ns
t _{d(off)}	Turn-off Delay Time	R _G =3.3Ω, V _{GS} =10V	-	18	-	ns
t _f	Fall Time	R _D =2.5Ω	-	3	-	ns
C _{iss}	Input Capacitance	V _{GS} =0V	-	590	940	pF
C _{oss}	Output Capacitance	V _{DS} =25V	-	90	-	pF
C _{rss}	Reverse Transfer Capacitance	f=1.0MHz	-	50	-	pF
R _g	Gate Resistance	f=1.0MHz	-	1.8	2.7	Ω

Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V _{SD}	Forward On Voltage ²	I _S =8A, V _{GS} =0V	-	-	1.3	V
t _{rr}	Reverse Recovery Time ²	I _S =8A, V _{GS} =0V dI/dt=100A/μs	-	18	-	ns
Q _{rr}	Reverse Recovery Charge		-	13	-	nC



P-CH Electrical Characteristics @T_j=25°C(unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units	
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =-250uA	-40	-	-	V	
ΔBV _{DSS} /ΔT _j	Breakdown Voltage Temperature Coefficient	Reference to 25°C, I _D =-1mA	-	-0.02	-	V/°C	
R _{DS(ON)}	Static Drain-Source On-Resistance ²	V _{GS} =-10V, I _D =-6A	-	-	72	mΩ	
		V _{GS} =-4.5V, I _D =-4A	-	-	92	mΩ	
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =-250uA	-0.8	-	-2.5	V	
g _{fs}	Forward Transconductance	V _{DS} =-10V, I _D =-6A	-	6	-	S	
I _{DSS}	Drain-Source Leakage Current (T _j =25°C)	V _{DS} =-40V, V _{GS} =0V	-	-	-1	uA	
		V _{DS} =-32V, V _{GS} =0V	-	-	-25	uA	
I _{GSS}	Gate-Source Leakage	V _{GS} =±20V	-	-	±100	nA	
Q _g	Total Gate Charge ²	I _D =-6A	-	7.3	12	nC	
Q _{gs}	Gate-Source Charge		V _{DS} =-30V	-	1.3	-	nC
Q _{gd}	Gate-Drain ("Miller") Charge		V _{GS} =-4.5V	-	3.6	-	nC
t _{d(on)}	Turn-on Delay Time ²	V _{DS} =-20V	-	6	-	ns	
t _r	Rise Time		I _D =-6A	-	17	-	ns
t _{d(off)}	Turn-off Delay Time		R _G =1Ω, V _{GS} =-10V	-	21	-	ns
t _f	Fall Time		R _D =3.33Ω	-	5	-	ns
C _{iss}	Input Capacitance	V _{GS} =0V	-	450	720	pF	
C _{oss}	Output Capacitance		V _{DS} =-25V	-	80	-	pF
C _{rss}	Reverse Transfer Capacitance		f=1.0MHz	-	60	-	pF
R _g	Gate Resistance	f=1.0MHz	-	5.6	8.4	Ω	

Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V _{SD}	Forward On Voltage ²	I _S =-6A, V _{GS} =0V	-	-	-1.3	V
t _{rr}	Reverse Recovery Time ²	I _S =-6A, V _{GS} =0V	-	22	-	ns
Q _{rr}	Reverse Recovery Charge		dI/dt=-100A/μs	-	14	-

Notes:

- 1.Pulse width limited by Max. junction temperature.
- 2.Pulse width ≤300us , duty cycle ≤2%.
- 3.N-CH , P-CH are same .



N-Channel




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. On-Resistance v.s. Gate Voltage




Fig 4. Normalized On-Resistance v.s. Junction Temperature




Fig 5. Forward Characteristic of Reverse Diode




Fig 6. On-Resistance vs. Drain Current



N-Channel




Fig 7. Gate Charge Characteristics




Fig 8. Typical Capacitance Characteristics




Fig 9. Maximum Safe Operating Area




Fig 10. Effective Transient Thermal Impedance




Fig 11. Transfer Characteristics




Fig 12. Gate Charge Waveform



AP4521GEH

P-Channel




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. On-Resistance v.s. Gate Voltage




Fig 4. Normalized On-Resistance v.s. Junction Temperature




Fig 5. Forward Characteristic of Reverse Diode




Fig 6. On-Resistance vs. Drain Current



P-Channel




Fig 7. Gate Charge Characteristics




Fig 8. Typical Capacitance Characteristics




Fig 9. Maximum Safe Operating Area




Fig 10. Effective Transient Thermal Impedance




Fig 11. Transfer Characteristics




Fig 12. Gate Charge Waveform