

DC - 18.0 GHz	464 Series	Model Numbers
Male/Female	Female/Female	Male/Male
ATT-0464-XX-SMA-02	ATT-464F-XX-SMA-02	ATT-464M-XX-SMA-02
XX = Attenuation Value: Select 01-30*dB in 1dB increments only		
<i>Wireless System Performance</i>		

DC - 26.5 GHz	465 Series	Model Numbers
Male/Female	Female/Female	Male/Male
ATT-0465-XX-SMA-02	ATT-465F-XX-SMA-02	ATT-465M-XX-SMA-02
XX = Attenuation Value: Select 01-30*dB in 1dB increments only		
<i>Wireless System Performance</i>		




Hex Body Types - Wireless System Performance


DC - 4.0 GHz	461 HEX Series	Model Numbers
Male/Female	Female/Female	Male/Male
ATT-0461-XX-HEX-02	ATT-461F-XX-HEX-02	ATT-461M-XX-HEX-02
XX = Attenuation Value: Select 01-30*dB in 1dB increments only		
<i>Wireless System Performance</i>		

DC - 18.0 GHz	464 HEX Series	Model Numbers
Male/Female	Female/Female	Male/Male
ATT-0464-XX-HEX-02	ATT-464F-XX-HEX-02	ATT-464M-XX-HEX-02
XX = Attenuation Value: Select 01-30*dB in 1dB increments only		
<i>Wireless System Performance</i>		


DC - 26.5 GHz	465 HEX Series	Model Numbers
Male/Female	Female/Female	Male/Male
ATT-0465-XX-HEX-02	ATT-465F-XX-HEX-02	ATT-465M-XX-HEX-02
XX = Attenuation Value: Select 01-30*dB in 1dB increments only		
<i>Wireless System Performance</i>		



Attenuation Value	Length A
1-12 dB	0.86
13-30 dB	1.02



Attenuation Value	Length A
1-12 dB	0.90
13-30 dB	1.03



Attenuation Value	Length A
1-12 dB	0.98
13-30 dB	1.12