





TCMD-20-S-10-01



TCMD-05-S-12-01

2mm IDC CABLE STRIPS TCMD SERIES

Mates with:
SMM, MMS

Features:

- Low profile, only (5,00mm) .200" assembled height
- Ask about our custom IDC design capabilities

Specifications:

TCMD
Insulator Material: Black Glass Filled Polyester
Terminal: Phosphor Bronze
Current Rating: 1A
Plating: 150µ" (3.8µm) Sn over 50µ" (1.27µm) Ni
Operating Temp Range: -40°C to +105°C
Wire: 28 AWG 7/36 Stranded, Tinned Copper with Gray PVC Insulator

TYPE STRIP	NO. PINS PER ROW	END OPTION	OVERALL LENGTH	01	TRANSFER OPTION	OTHER OPTION
	-05, -08, -10, -12, -13, -15, -17, -20, -22, -25 (Call for other sizes)		- "XX" = Assembled Length		Leave blank for -S and -D End Options. Specify "-N" for -T End Option	
		-S = Single End	-D = Double End		-P "XX" = Position Polarization Specify "XX" as position number. Requires Transfer End. Only Socket is polarized.	-D "XX" = Daisy Chain Specify "XX" as position number. Requires Transfer End. Only Socket is polarized.
		-T = Transfer End			-R = Reversed	-M = Middle Reverse
				-RW = Reverse Wiring Blue or black wire opposite position #1	-O = Outside Reverse	

TCMD = Terminal Strip

Dimensions shown: (4.00) 158, (5.08) 200, (8.05) 120, (1.00) .03937, (2.00) .0787, (0.50) .020 50, (2.00) .0787, (2.00) .0787.

Note: TCMD Series assemblies are non-standard, non-returnable.