




- 1 THE TIP OF THE CONTACT POSTS WILL FALL WITHIN .025 DIAMETER TRUE POSITION OF EACH OTHER.
- 2 PARTS TO BE ASSEMBLED BY AMP INC.
- 3 AMP, PART NUMBER AND DATE CODE MARKED ON EITHER SIDE.

.520 [13.21]	3	.022X.036 POST
.370 [9.40]	2	
.220 [5.59]	1	
.670 [17.02]	3	.025X.025 POST
.456 [11.58]	2	
.242 [6.15]	1	
"A"	NUMBER OF TERMINATIONS	TYPE OF POST

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHALL BE ADVISED FOR THE LATEST REVISION.		DWG: T. THOMPSON 09-08-95		AMP INCORPORATED Harrisburg, PA 17105-3608	
DIMENSIONS: IN [mm]		CHK: D. MUMMEY 09-08-95		AMP INCORPORATED	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPD: D. MUMMEY 09-08-95		54 POSITION, HDR, RECEPTACLE W/ JACKSCREW	
Ø PLC ±.005 (0.13)		PRODUCT SPEC		SIZE: A1	
APPLIC. SPEC		CAGE CODE		DRAWING NO: C=204690	
MATERIAL: SEE TABLE		WEIGHT: -		SCALE: 8:1	
FINISH: SEE TABLE		CUSTOMER DRAWING		SHEET 13 OF 13	

