


► Expert Range



Male socket.

Horizontal closed double deck sockets without offset.



Plug RECTANGULAR SHAPE

Pin 0.8 x 0.8 x 3.5 mm
.031" x .031" x .138"


P.C.B. thickness ≤ 2.4 mm .094"

P.C.B. holes $\varnothing$ 1.2 mm .047"

Body : UL94 V0 - PA

Grey ☐

Spacing 3.5 mm .138"




Socket L 252 800 11
compatible with :



L 242 200 01



Socket L 252 800 31
compatible with :



L 242 200 31

Ordering details

N. Poles	Weight kg	Packaging	L. mm	Order code
4	0.0018	50	8.7	1SSA 252 804 R1100
6	0.0027	50	12.2	1SSA 252 806 R1100
8	0.0036	50	15.7	1SSA 252 808 R1100
10	0.0045	50	19.2	1SSA 252 810 R1100
12	0.0054	50	22.7	1SSA 252 812 R1100

Other numbers of poles, consult us



Technical data


		IEC	UL	CSA
Wire size				
Screw	Solid wire			
	Stranded wire			
	With ferrule			
Rated voltage		160 V		
Rated current		8 A		
Short-circuit current				
Rated wire size / Gauge				
Storage temperature range		-20 ~ +80 °C		
Insulation resistance		≥ 10 ⁹ Ω		
Wire stripping length				
Recommended screwdriver				
Recommended torque				
Protection		IP 20 / NEMA 1		

Accessories

Rep.	Description	Type	Order code	Packaging	Weight kg
1	Coding peg		1SSA 299 084 R0600	50	0.0005

Other versions, please consult us :

Horizontal closed double deck sockets without offset with flanges and inserts.



L 252 800 31

