

TO-202 Plastic Package Transistors (PNP)

Maximum Ratings						Electrical Characteristics (Ta=25°C, Unless Otherwise Specified)														
Type No.	V _{CBO} (V) Min	V _{CEO} (V) Min	V _{EB0} (V) Min	P _D (W) Ta=25 °C	I _C (A)	I _{CBO} (μA) Max	V _{CB} (V) @	h _{FE}		Ⓢ I _C & (mA)	V _{CE} (V)	V _{CE(SAT)} (V) &		V _{BE(SAT)} (V) Max	I _C (mA) @	C _{ob} (pF) Max	I _f (MHz) Min	@ Max	I _C (mA)	CDIL Case Style
BD814	45	45	5	2				40	250	150	2	0.6		1000		3				TO-202
BD816	60	60	5	2				40	250	150	2	0.6		1000		3				TO-202
BD818	100	80	5	2				40	250	150	2	0.6		1000		3				TO-202
BD826	45	45	5	2	1	0.1	30	25		5	2	0.5		500			75	50		TO-202
								40	250	150	2									
								25		500	2									
BD828	60	60	5	2	1	0.1	30	25		5	2	0.5		500			75	50		TO-202
								40	250	150	2									
								25		500	2									
BD830	100	80	5	2	1	0.1	30	25		5	2	0.5		500			75	50		TO-202
								40	250	150	2									
								25		500	2									
BD840	45	45	5	2				25		5	2	0.8		1000		50				TO-202
								25		1000	2									
								40	250	150	2									
BD842	60	60	5	2				25		5	2	0.8		1000		50				TO-202
								25		1000	2									
								40	250	150	2									
BD844	100	80	5	2				25		5	2	0.8		1000		50				TO-202
								25		1000	2									
								40	250	150	2									
BF760	250	250	5	2	0.5	0.2	150	25		1	10	0.8		30	3	20	200	10		TO-202
								40	180	30	10									
BF761	300	300	5	2	0.5	0.2	200	25		1	10	0.8		30	3	20	200	10		TO-202
								40	180	30	10									
BF762	350	350	5	2	0.5	0.2	250	25		1	10	0.8		30	3	20	220	10		TO-202
								40	180	30	10									
CSA743	50	50	5	2	1	5	50	60	200	50	4	1.5		1000	30	75	120	30		TO-202
								20		1000	4									
CSA743A	80	80	5	2	1	5	50	60	200	50	4	1.5		1000	30	75	120	30		TO-202
								20		1000	4									
CSA743B	50	50	5	2	1	5	50	60	120	50	4	1.5		1000	30	75	120	30		TO-202
								20		1000	4									
CSA743C	50	50	5	2	1	5	50	100	200	50	4	1.5		1000	30	75	120	30		TO-202
								20		1000	4									